


## 170M4665

#### 170M4665 Information



Part Number	170M4665	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE SQ 550A 700VAC RECTANGULAR	
Package	Rectangular, Blade	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



Request a Quote

### 170M4665 Specifications

Manufacturer Part Number170M4665ManufacturerEatonCategoryCircuit ProtectionPackageElectrical, Specialty FusesPackageRetangular, BladeStries-Fuse TypeSquareOurrent RatingStoAVoltage Rating - DC-Voltage Rating - DC-Applications-ApplicationsElectrical, IndustrialCarsent Spectra (Carsent Spectra (C		
CategoryCircuit Protection Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareFuse TypeSobaCurrent Rating500AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFaturesIndicatingOperating Temperature-ApprovalsCE, CSA, UROperating Temperature200AMounting TypeBid MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm)	Manufacturer Part Number	170M4665
Field of the section	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating550AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating TemperatureSolt AutomationMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 59.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareCurrent Rating550AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature200kABreaking Capacity @ Rated VoltageBolt MountiPackage / CaseRectangulan, BladeSize / Dimension1,609" Lx 2,087" Wx 2,717" H (50.00mm x 53.00mm x 69.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareFuse TypeSquareCurrent RatingS50AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature200KAFeatures Que Acting VoltageSolt Mounting TypePackage / CaseRectangulandeFeaturesStol MountStol / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 50.00mm)	Package	Rectangular, Blade
Current Rating550AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated VoltageBolt MountMounting TypeBolt MountPackage / CaseRectangulandeSize / Dimension1,969" L x 2,087" W x 2,717" H (50.00mm x 59.00mm)	Series	-
Voltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated VoltageBolt MountMounting TypeBolt MountPackage / CaseRectangular BladeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Fuse Type	Square
Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage00kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Current Rating	550A
Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2,087" W x 2,717" H (50.00mm x 53.00mm x 69.00mm)	Voltage Rating - AC	700V
ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2,087" W x 2,717" H (50,00mm x 53,00mm x 69,00mm)	Voltage Rating - DC	-
FeaturesIndicatingFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Response Time	-
Class -   Approvals CE, CSA, UR   Operating Temperature -   Breaking Capacity @ Rated Voltage 200kA   Mounting Type Bolt Mount   Package / Case Rectangular, Blade   Size / Dimension 1,969" L x 2,087" W x 2,717" H (50.00mm x 53.00mm x 69.00mm)	Applications	Electrical, Industrial
ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Class	-
Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Approvals	CE, CSA, UR
Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Operating Temperature	-
Package / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)
		Report errors?

#### 170M4665 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M4665, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com