

# 170M4695

#### 170M4695 Information



For Reference Only

Part Number	170M4695	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE SQ 500A 1.3KVAC RECTANGULAR	
Package	Rectangular, Blade	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## 170M4695 Specifications

ManufacturerEatonCategoryCircuit ProtectionElectrical, Specialty FusesPackageRectangular, BladeSeries-SeriesSquareCurrent RatingS00AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseScusgular, BladeSize / Dimension2,913" L x 2.087" W x 2.717" H (74.00mm x 53.00mm x 69.00mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating500AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature100ABreaking Capacity @ Rated Voltage100AAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.93" L x 2.087" W x 2.71" H (74.00mm x 53.00mm x 69.00mm)	Manufacturer Part Number	170M4695
Filedrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating500AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature100kABreaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2,913" L x 2.087" W x 2.717" H (74.00mm x 53.00mm x 69.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating500AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.913" L x 2.087" W x 2.717" H (74.00mm x 53.00mm x 69.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareCurrent Rating500AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature100kABreaking Capacity @ Rated VoltageBolt MountMounting TypeBolt MountPackage / CaseScusy I'' W x 2.717" H (74.00mm x 53.00mm x 69.00mm)		Electrical, Specialty Fuses
Fuse Type Square   Fuse Type Square   Current Rating S00A   Voltage Rating - AC 1300V (1.3kV)   Voltage Rating - DC -   Response Time -   Applications Electrical, Industrial   Features Indicating   Class -   Approvals CSA, UR   Operating Temperature IOkA   Breaking Capacity @ Rated Voltage Bolt Mounti   Package / Case Rectangular, Blade   Size / Dimension 2.913" L x 2.087" W x 2.717" H (74.00mm x 53.00mm x 69.00mm)	Package	Rectangular, Blade
Current Rating500AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated VoltageBolt MountMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.913" L x 2.087" W x 2.717" H (74.00mm x 59.00mm)	Series	-
Voltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature100kABreaking Capacity @ Rated VoltageBolt MountMounting TypeBolt MountPackage / Case.Size / Dimension2.913" L x 2.087" W x 2.717" H (74.00mm x 53.00mm x 69.00mm)	Fuse Type	Square
Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.913" L x 2.087" W x 2.717" H (74.00m x 53.00m x 69.00m)	Current Rating	500A
Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2913" L x 2.087" W x 2.717" H (74.00mm x 53.00mm x 69.00mm)	Voltage Rating - AC	1300V (1.3kV)
ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.913" L x 2.087" W x 2.717" H (74.00mm x 53.00mm x 69.00mm)	Voltage Rating - DC	-
FeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.913" L x 2.087" W x 2.717" H (74.00mm x 53.00mm x 69.00mm)	Response Time	-
Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.913" L x 2.087" W x 2.717" H (74.00mm x 53.00mm x 69.00mm)	Applications	Electrical, Industrial
ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.913" L x 2.087" W x 2.717" H (74.00mm x 53.00mm x 69.00mm)	Features	Indicating
AOperating TemperatureBreaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.913" L x 2.087" W x 2.717" H (74.00mm x 53.00mm x 69.00mm)	Class	-
Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.913" L x 2.087" W x 2.717" H (74.00mm x 53.00mm x 69.00mm)	Approvals	CSA, UR
Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.913" L x 2.087" W x 2.717" H (74.00mm x 53.00mm x 69.00mm)	Operating Temperature	-
Package / CaseRectangular, BladeSize / Dimension2.913" L x 2.087" W x 2.717" H (74.00mm x 53.00mm x 69.00mm)	Breaking Capacity @ Rated Voltage	100kA
Size / Dimension 2.913" L x 2.087" W x 2.717" H (74.00mm x 53.00mm x 69.00mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	2.913" L x 2.087" W x 2.717" H (74.00mm x 53.00mm x 69.00mm)
		Report errors?

#### 170M4695 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M4695, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com