

# 170M4762

### 170M4762 Information



For Reference Only

Part Number	170M4762	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE SQ 400A 700VAC RECTANGULAR	
Package	Rectangular, Blade	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



Request a Quote

## 170M4762 Specifications

Manufacturer Part Number170M4762ManufacturerEatonCategoryCircuit ProtectionElectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating400AVoltage Rating - DC-Voltage Rating - DC-ApplicationsElectrical, IndustrialFaturesIndicatingClass-ApprovalsCE, CSA, UROperating TypeSold Mouting TypeMounting TypeBolt MoutFackage / CaseRectangular, BladeSize / Dimension1,969° Lx 2,087° Wx 2,717° H (50,00mm x 53,00mm x 69,00mm)		
CategoryCircuit ProtectionBectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating400AVoltage Rating - AC700VVoltage Rating - DC-ApplicationsElectrical, IndustrialApplicationsElectrical, IndustrialClass-ApprovalsCE, CSA, UROperating Temperature00kABreaking Capacity @ Rated VoltageBit MountMounting TypeBit MountFackage / CaseRectangular, BladeSize / Dimension1.909" L x 2.087" W x 2.717" H (50.00mm x 53.00mm)	Manufacturer Part Number	170M4762
PackageElectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating400AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature900KABreaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969° L x 2,087° W x 2,717° H (50.00mm x 53.00mm x 69.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating400AVoltage Rating - AC700VVoltage Rating - DC-Applications-ApplicationsElectrical, IndustrialFeaturesIndicatingsOperating Temperature-Operating TemperatureSQUARMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareFuse Type400ACurrent Rating400AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangulandeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 59.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareFuse Type400AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Mounting TypeBoth MountFackage / CaseSolt MountFackage / CaseIndicating Ale MountFackage / CaseSolt MountFackage / CaseIndicating Ale MountFackage / CaseSolt MountFackage / CaseIndicating Ale MountFackage / CaseIndicat	Package	Rectangular, Blade
Current Rating400AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated VoltageS00kAMounting TypeBolt MountPackage / Case.Size / Dimension1,969" L x 2,087" W x 2,717" H (50.00mm x 59.00mm)	Series	-
Voltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated VoltageBolt MountPackage / CaseRectangulareSize / Dimension1,969" L x 2,087" W x 2,717" H (50.00mm x 50.00mm x 69.00mm)	Fuse Type	Square
Voltage Rating - DC.Response Time.ApplicationsElectrical, IndustrialApplicationsIndicatingClass.ApprovalsCE, CSA, UROperating Temperature.Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / Case.Size / Dimension1.969" L x 2.087" W x 2.717" H (50.00m x 50.00m x 50.0	Current Rating	400A
Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2,087" W x 2,717" H (50.00mm x 53.00mm x 69.00mm)	Voltage Rating - AC	700V
ApplicationsElectrical, IndustrialApplicationsIndicatingFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2,087" W x 2,717" H (50.00mm x 53.00mm x 69.00mm)	Voltage Rating - DC	-
FeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangulang BaleSize / Dimension1,969" L x 2,087" W 2,071" H (50,00mm, 25,00mm, 26,00mm)	Response Time	-
Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 59.00mm)	Applications	Electrical, Industrial
ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Class	-
Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Approvals	CE, CSA, UR
Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Operating Temperature	-
Package / Case Rectangular, Blade   Size / Dimension 1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular, Blade
Report errors'	Size / Dimension	1.969" L x 2.087" W x 2.717" H (50.00mm x 53.00mm x 69.00mm)
		Report errors?

#### 170M4762 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M4762, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com