

170M4832

170M4832 Information

Heisener.com	Part Number	170M4832
	Manufacturer	Eaton
	Category	Circuit Protection Electrical, Specialty Fuses
	Description	FUSE 160A 1000V 00TN/80 AR
	Package	Rectangular, Blade
		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



Request a Quote

170M4832 Specifications

Series*Fuse TypeSquareCurrent Rating-Voltage Rating - AC-Voltage Rating - DC-Response Time-Applications-Features-Class-Approvals-Approvals-Approvals-Conserting-Approvals-Ap			
Category Circuit Protection Electrical, Specialty Fuses Package Rectangular, Blade Series * Fuse Type Square Current Rating - Voltage Rating - AC - Voltage Rating - DC - Applications - Applications - Fatures - Class - Approvals - Operating Temperature - Mounting Type - Package/ Case - Ster Jpienssion -	Manufacturer Part Number	170M4832	
Electrical, Specialty FusesPackageRectangular, BladeSeries*Fuse TypeSquareCurrent Rating-Voltage Rating - AC-Voltage Rating - DC-Response Time-Applications-Features-Class-Operating Temperature-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.126" L x 1.181" W x 2.008" H (54.00mm x 30.00mm x 51.00mm)	Manufacturer	Eaton	
PackageRectangular, BladeSeries*Fuse TypeSquareCurrent Rating-Voltage Rating - AC-Voltage Rating - DC-Response Time-Applications-Features-Class-Operating Temperature-Operating Capacity @ Rated Voltage-Mounting Type-Package / CaseSolt MountPackage / CaseSolt Last 1.181" W x 2.008" H (54.00mm x 51.00mm)	Category	Circuit Protection	
Series*Fuse TypeSquareCurrent Rating-Voltage Rating - AC-Voltage Rating - DC-Response Time-Applications-Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeBolt MountPackage / CaseRectangulant, BladeSize / Dimension:2126 "L x 1.181" W x 2.008" H (54.00mm x 51.00mm)		Electrical, Specialty Fuses	
StriksFuse TypeSquareCurrent Rating-Voltage Rating - AC-Voltage Rating - DC-Response Time-Applications-Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeBolt MountPackage / CaseScalaguard BladeSize / Dimension2.126" L x 1.181" W x 2.008" H (54.00mm x 51.00mm)	Package	Rectangular, Blade	
Current Rating-Voltage Rating - AC-Voltage Rating - DC-Response Time-Applications-Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting Type-Package / Case-Size / Dimension-Size / Dimension </td <td>Series</td> <td colspan="2">*</td>	Series	*	
Voltage Rating - AC-Voltage Rating - DC-Response Time-Applications-Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeBolt MountPackage / CaseRectangulandeSize / Dimension2.126" L x 1.181" W x 2.008" H (54.00mm x 51.00mm)	Fuse Type	Square	
Voltage Rating - DC-Response Time-Applications-Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Nounting TypeBolt MountPackage / CaseRectangulandeSize / Dimension2.126"L x 1.181"W x 2.008"H (54.00mm x 51.00mm)	Current Rating	-	
Response Time-Applications-Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension:126" L x 1.181" W x 2.008" H (54.00mm x 51.00mm)	Voltage Rating - AC	-	
Applications-Applications-Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.126" L x 1.181" W x 2.008" H (54.00mm x 50.00mm x 51.00mm)	Voltage Rating - DC	-	
Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.126" L x 1.181" W x 2.008" H (54.00mm x 51.00mm)	Response Time	-	
Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.126" L x 1.181" W x 2.008" H (54.00mm x 51.00mm)	Applications	-	
Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.126" L x 1.181" W x 2.008" H (54.00mm x 51.00mm)	Features	-	
Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.126" L x 1.181" W x 2.008" H (54.00mm x 30.00mm x 51.00mm)	Class	-	
Breaking Capacity @ Rated Voltage-Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.126" L x 1.181" W x 2.008" H (54.00mm x 30.00mm x 51.00mm)	Approvals	-	
Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.126" L x 1.181" W x 2.008" H (54.00mm x 30.00mm x 51.00mm)	Operating Temperature	-	
Package / CaseRectangular, BladeSize / Dimension2.126" L x 1.181" W x 2.008" H (54.00mm x 30.00mm x 51.00mm)	Breaking Capacity @ Rated Voltage	-	
Size / Dimension 2.126" L x 1.181" W x 2.008" H (54.00mm x 30.00mm x 51.00mm)	Mounting Type	Bolt Mount	
	Package / Case	Rectangular, Blade	
Report errors?	Size / Dimension 2.126" L x 1.181" W x 2.008" H (54.00mm x 30.00mm x 51.00mm		
		Report errors?	

170M4832 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M4832, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com