

170M5161

170M5161 Information



For Reference Only

Part Number	170M5161	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE SQ 550A 700VAC RECTANGULAR	
Package	Rectangular, Blade	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



170M5161 Specifications

Manufacturer Part NumberI70M5161ManufacturerEatonCategoryCircuit ProtectionPackageRectanglary FusesPackageRectangulary BladeStries-Fuse TypeSquareOurrent RatingStoAVoltage Rating - DC-Voltage Rating - DC-ApplicationsElectrical, IndustrialApprovals-Oursent String-Applorations-Approvals-Operating Theorem-Oursent String-Outsent String-Applorations-Approvals-Operating Theorem-Operating Theorem-Operating Type-Outsent String Category-Operating Type-Operating Type-Applorations-Approvals-Operating Type-Operating Type-Operating Type-Operating Type-Applorations-Applorations-Applorations-Operating Type-Operating Type-<		
CategoryCircuit Protection Electrical, Specialty FusesPackageRectangular, BladeSories-Fuse TypeSquareFuse TypeSolaCurrent Rating505AVoltage Rating - AC700VVoltage Rating - DC-ApplicationsElectrical, IndustrialResponse Time-FaturesIndicatingOperating Temperature-ApprovalsCE, CSA, UROperating Temperature200AMounting TypeBit MountPackage / CaseSolaSite / DimensionStolagular, BladeSite / DimensionSolagular, BladeSite / DimensionStolagular, BladeSite / DimensionSologular, Stolagular, BladeSite / DimensionSologular, Stolagular, BladeSite / DimensionSologular, Stolagular, BladeSite / DimensionSologular, Stolagular, Blade	Manufacturer Part Number	170M5161
Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating550AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature200kABreaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2,402" W x 2,953" H (50.00mm x 51.00mm x 75.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating550AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature200KAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.402" W x 2.953" H (50.00mm x 75.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareCurrent Rating550AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature200ABreaking Capacity @ Rated VoltageBolt Mounting TypePackage / CaseRectangulang BaldeSize / Dimension1,609" L x 2,402" W x 2,953" H (50.00mm x 61.00mm x 75.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareFuse TypeSquareCurrent RatingS50AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature200KABreaking Capacity @ Rated VoltageSolt Mounting TypePackage / CaseRectangulane BladeSize / Dimension1.969" L x 2.402" W x 2.953" H (50.00mm x 75.00mm)	Package	Rectangular, Blade
Current Rating550AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated VoltageBolt MountMounting TypeBolt MountPackage / CaseRectangulandeSize / Dimension1.969" L x 2.402" W x 2.953" H (50.00mm x 75.00mm)	Series	-
Voltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature200kABreaking Capacity @ Rated VoltageBolt MountMounting TypeBolt MountPackage / Case.Size / Dimension1.969" L x 2.402" W x 2.953" H (50.00mm x 61.00mm x 75.00mm)	Fuse Type	Square
Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature00KAFeaking Capacy @ Rated VoltageBolt MountMounting TypeBolt MountPackage / CaseRectangulandeSize / Dimension1.969° L x 2.402° W x 2.953° H (50.0000 m x 50.0000 m x 50.0000 m x 50.0000 m x 50.0000 m x 50.00000 m x 50.000000 m x 50.000000 m x 50.000000 m x 50.000000 m x 50.0000000000000000000000000000000000	Current Rating	550A
Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.402" W x 2.953" H (50.00mm x 75.00mm)	Voltage Rating - AC	700V
ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2,402" W x 2,953" H (50.00mm x 61.00mm x 75.00mm)	Voltage Rating - DC	-
FeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2,402" W x 2,953" H (50.00mm x 61.00mm x 75.00mm)	Response Time	-
Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2.402" W x 2.953" H (50.00mm x 61.00mm x 75.00mm)	Applications	Electrical, Industrial
ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.402" W x 2.953" H (50.00mm x 61.00mm x 75.00mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.402" W x 2.953" H (50.00mm x 61.00mm x 75.00mm)	Class	-
Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.402" W x 2.953" H (50.00mm x 61.00mm x 75.00mm)	Approvals	CE, CSA, UR
Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.402" W x 2.953" H (50.00mm x 61.00mm x 75.00mm)	Operating Temperature	-
Package / Case Rectangular, Blade Size / Dimension 1.969" L x 2.402" W x 2.953" H (50.00mm x 61.00mm x 75.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.969" L x 2.402" W x 2.953" H (50.00mm x 61.00mm x 75.00mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	1.969" L x 2.402" W x 2.953" H (50.00mm x 61.00mm x 75.00mm)
		Report errors?

170M5161 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M5161, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com