

170M5260

170M5260 Information



Part Number	170M5260	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE SQ 500A 700VAC RECTANGULAR	
Package	Rectangular, Blade	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



170M5260 Specifications

Manufacturer Part Number I70M5260 Manufacturer Eaton Category Circuit Protection Package Electrical, Specialty Fuses Package Rectangular, Blade Series - Fuse Type Square Current Rating S00A Voltage Rating - AC 700V Voltage Rating - DC - Applications Electrical, Industrial Applications Electrical, Industrial Operating Temperature - Approvals CE, CSA, UR Operating Temperature SoltaA Mounting Type Bott Mount Package / Case Rectangular, Blade Size / Dimension Size / Dimension		
CategoryCircuit Protection Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareFuse TypeSobACurrent Rating500AVoltage Rating - AC700VVoltage Rating - DC-ApplicationsElectrical, IndustrialResponse Time-ApplicationsElectrical, IndustrialFaturesIndicatingOperating Temperature-ApprovalsCE, CSA, UROperating Temperature300AMounting TypeSobAPackage / CaseSolotASiev / DimensionSctongular, BladeSiev / Dimension1.60° L x 2.40° W x 3.031° H (50.00mm x 7.00mm)	Manufacturer Part Number	170M5260
Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurren Rating500AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature200kABreaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2,402" W x 3,031" H (50.00mm x 71.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating500AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating TemperatureS00KAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareCurrent Rating500AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature200kABreaking Capacity @ Rated VoltageBolt MountiPackage / CaseRectangulang BaleSize / Dimension1,609" L x 2,402" W x 3,031" H (50.00mm x 61.00mm x 77.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareFuse TypeSquareCurrent RatingS00AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature200KAFeaking Capacity @ Rated VoltageBiol MountiPackage / CaseRectangulaneSize / Dimension1.969" L x 2.402" W x 3.031" H (50.00mm x 77.00mm)	Package	Rectangular, Blade
Current RatingSOAVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Beaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangulandeSize / Dimension1,969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)	Series	-
Voltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated VoltageBolt MountMounting TypeBolt MountPackage / CaseRectangulandeSize / Dimension1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)	Fuse Type	Square
Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage00kAMounting TypeBolt MountPackage / CaseRectangulandeSize / Dimension1.969" L x 2.402" W x 3.031" H (50.00mm x 70.00mm)	Current Rating	500A
Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.402" W x 3.031" H (50.00mm x 77.00mm)	Voltage Rating - AC	700V
ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)	Voltage Rating - DC	-
FeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage20kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2,402" W x 3,031" H (50.00mm x 61.00mm x 77.00mm)	Response Time	-
Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)	Applications	Electrical, Industrial
ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)	Class	-
Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)	Approvals	CE, CSA, UR
Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)	Operating Temperature	-
Package / CaseRectangular, BladeSize / Dimension1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)
		Report errors?

170M5260 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M5260, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com