

## 170M5268

#### 170M5268 Information



| Part Number  | 170M5268   |  |
|--------------|--|--|
| Manufacturer | Eaton  |  |
| Category     | Circuit Protection<br>Electrical, Specialty Fuses  |  |
| Description  | FUSE SQ 1.25KA 700VAC RECTANGLR  |  |
| Package      | Rectangular, Blade   |  |
|              | For the pricing/inventory/lead time, please contact<br>us<br>Website: https://www.heisener.com<br>E-mail: salesdept@heisener.com |  |



Request a Quote

For Reference Only

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### 170M5268 Specifications

| Manufacturer Part Number170M5268ManufacturerEatonCategoryCircuit ProtectionElectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating1.25kAVoltage Rating - DC-Voltage Rating - DC-ApplicationsElectrical, IndustrialResonse Time-Class-ApprovalsCic CSA, UROperating Temperature-Preaking Capacity @ Rated Voltage200kAMounting TypeBit MountPackage / CaseSci Cagual, BladeSiz / DimensionMoutSiz / DimensionSci Cagual, BladeSiz / DimensionSci Cagual, Blade <th></th> <th></th> |                                   |  |
|--|-----------------------------------|--|
| CategoryCircuit Protection<br>Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareFuse TypeSquareCurrent Rating1.25kAVoltage Rating - AC700VVoltage Rating - DC-ApplicationsElectrical, IndustrialResponse Time-ApplicationsElectrical, IndustrialFaturesIndicatingOperating Temperature-ApprovalsCE, CSA, UROperating Temperature300AMounting TypeBid MountPackage / CaseRectangular, BladeSize / Dimension1.960° Lx 2.402° Wx 3.031° H (50.00mm x 7.00mm)  | Manufacturer Part Number          | 170M5268   |
| Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating1.25kAVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature200kABreaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.402" W x 3.031" H (50.00mm x 71.00mm)   | Manufacturer                      | Eaton  |
| PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating1.25kAVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)  | Category                          | Circuit Protection   |
| Series-Fuse TypeSquareCurrent Rating1.25kAVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature200kABreaking Capacity @ Rated VoltageBolt MountPackage / CaseRectangulan, BladeSize / Dimension1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)   |                                   | Electrical, Specialty Fuses                                  |
| Fuse TypeSquareFuse TypeSquareCurrent Rating1.25kAVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature20kABreaking Capacity @ Rated VoltageSolt Mounting TypePackage / CaseRectangulane BaleSize / Dimension1.969" L x 2.402" W x 3.031" H (50.00mm x 77.00mm)   | Package                           | Rectangular, Blade   |
| Current Rating1.25kAVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated VoltageBolt MountMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)  | Series                            | -  |
| Voltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature200kABreaking Capacity @ Rated VoltageBolt MountMounting TypeBolt MountPackage / Case.Size / Dimension1.969" L x 2.402" W x 3.031" H (50.00mm x 77.00mm)   | Fuse Type                         | Square   |
| Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature00KAFeaking Capacy @ Rated VoltageBolt MountMounting TypeBolt MountPackage / CaseRectangulandeSize / Dimension1.969" L x 2.402" W x 3.031" H (50.00000000000000000000000000000000000  | Current Rating                    | 1.25kA   |
| Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)  | Voltage Rating - AC               | 700V   |
| ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)  | Voltage Rating - DC               | -  |
| FeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage20kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2,402" W x 3,031" H (50.00mm x 61.00mm x 77.00mm)   | Response Time                     | -  |
| Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)  | Applications                      | Electrical, Industrial                                       |
| ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)  | Features                          | Indicating   |
| Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)  | Class                             | -  |
| Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)  | Approvals                         | CE, CSA, UR  |
| Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)  | Operating Temperature             | -  |
| Package / Case Rectangular, Blade   Size / Dimension 1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)  | Breaking Capacity @ Rated Voltage | 200kA  |
| Size / Dimension 1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)  | Mounting Type                     | Bolt Mount   |
|  | Package / Case                    | Rectangular, Blade   |
| Report errors?   | Size / Dimension                  | 1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm) |
|  |                                   | Report errors?   |

#### 170M5268 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M5268, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com