

# 170M5361

#### 170M5361 Information



Part Number	170M5361	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE SQ 550A 700VAC RECTANGULAR	
Package	Rectangular, Blade	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

## For Reference Only

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### 170M5361 Specifications

Manufacturer Part NumberI70M5361ManufacturerEatonCategoryCircuit ProtectionElectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent RatingStoAVoltage Rating - DC-Voltage Rating - DC-ApplicationsElectrical, IndustrialApprovalsElectrical, IndustrialClass-ApprovalsSAGAOperating Temperature-ApprovalsSAGAApprovals-Approvals-Approvals-Mounting Type-Aplacaque (Case)-Aplacaque (Case)-Size / Dimension-Size / Dimension- <th></th> <th></th>		
CategoryCircuit Protection Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareFuse TypeSolaCurrent Rating500AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFaturesIndicatingApprovalsCSA, UROperating Temperature-ApprovalsCSA, URNouting TypeSolaAnder Stanger Agent A	Manufacturer Part Number	170M5361
Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating550AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating TemperatureSolokABreaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2,402" W x 3,031" H (50.00mm x 61.00mm x 77.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating550AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating TemperatureSolokAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareCurrent Rating550AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature200kABreaking Capacity @ Rated VoltageBolt MountPockage / CaseRectangular, BladeSize / Dimension1,969" L x 2,402" W x 3,031" H (50.00mm x 61.00mm x 77.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareFuse TypeSquareCurrent RatingS50AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated VoltageSOMAMounting TypeBol MountPackage / CaseRectangulandSize / Dimension1.969" L x 2.402" W x 3.031" H (50.00mm x 77.00mm)	Package	Rectangular, Blade
Curren Rating550AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature00KAReaking Capacity @ Rated VoltageBid MountPackage / CaseRectangulandSize / Dimension1.969" L x 2.402" W x 3.031" H (50.00mm x 7.00mm)	Series	-
Voltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature200kABreaking Capacity @ Rated VoltageBolt MountMounting TypeBolt MountPackage / Case.Size / Dimension1.969" L x 2.402" W x 3.031" H (50.00mm x 77.00mm)	Fuse Type	Square
Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.402" W x 3.031" H (50.00mm x 7.00mm)	Current Rating	550A
Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2,402" W x 3,031" H (50.00mm x 61.00mm x 77.00mm)	Voltage Rating - AC	700V
ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2,402" W x 3,031" H (50,00mm x 61,00mm x 77,00mm)	Voltage Rating - DC	-
FeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangulare, BladeSize / Dimension1,969" L x 2,402" W x 3,031" H (50,00m x 61,00m x 77,00m x	Response Time	-
Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)	Applications	Electrical, Industrial
ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1,969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)	Class	-
Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)	Approvals	CSA, UR
Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)	Operating Temperature	-
Package / CaseRectangular, BladeSize / Dimension1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)
		Report errors?

#### 170M5361 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M5361, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com