

170M5362 Information



For Reference Only

Part Number 170M5362 Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE SQ 630A 700VAC RECTANGULAR

Package Rectangular, Blade

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









170M5362 Specifications

Manufacturer Part Number 170M5362 Manufacturer Eaton Category Circuit Protection Package Rectangular, Blade Series - Fuse Type Square Current Rating 630A Voltage Rating - AC 700V Voltage Rating - DC - Response Time - Applications Electrical, Industrial Features Indicating Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating630AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)	Manufacturer Part Number	170M5362
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating630AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating630AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)	Category	Circuit Protection
Series - Fuse Type Square Current Rating 630A Voltage Rating - AC 700V Voltage Rating - DC - Response Time - Applications Electrical, Industrial Features Indicating Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareCurrent Rating630AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)	Package	Rectangular, Blade
Current Rating 630A Voltage Rating - AC 700V Voltage Rating - DC - Response Time Applications Electrical, Industrial Features Indicating Class Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.969" L x 2.402" W x 3.031" H (50.00mm x 77.00mm)	Series	-
Voltage Rating - AC Voltage Rating - DC Response Time Applications Electrical, Industrial Indicating Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 700V 700V 700V 700V 61000 CISS - COMMA Fleetrical, Industrial Fleetrical, Indu	Fuse Type	Square
Voltage Rating - DC Response Time - Applications Electrical, Industrial Features Indicating Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension	Current Rating	630A
Response Time Applications Electrical, Industrial Features Indicating Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension - Breaking Capacity @ Rated Voltage Response Time - Bolt Mount - Breaking Capacity @ Rated Voltage Bolt Mount - Bolt Mou	Voltage Rating - AC	700V
Applications Electrical, Industrial Features Indicating Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)	Voltage Rating - DC	-
Features Indicating Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)	Response Time	-
Class - CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)	Applications	Electrical, Industrial
Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage Bolt Mount Package / Case Rectangular, Blade Size / Dimension CSA, UR - Bolt Mount - Breaking Capacity @ Rated Voltage Bolt Mount Bolt Mount 1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)	Features	Indicating
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)	Approvals	CSA, UR
Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)	Operating Temperature	-
Package / Case Rectangular, Blade Size / Dimension 1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	1.969" L x 2.402" W x 3.031" H (50.00mm x 61.00mm x 77.00mm)
		Report errors?

170M5362 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

170M5362 Payment Methods



















170M5362 Shipping Methods













If you have any question about 170M5362, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com