

170M5742

170M5742 Information



For Reference Only

Part Number	170M5742	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE SQ 400A 1.3KVAC RECTANGULAR	
Package	Rectangular, Blade	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



170M5742 Specifications

Manufacturer Eaton Category Circuit Protection Electrical, Specialty Fuses Electrical, Specialty Fuses Package Rectangular, Blade Series - Fuse Type Square Current Rating 400A Voltage Rating - AC 1300V (1.3kV) Voltage Rating - DC - Response Time - Applications Electrical, Industrial Features Indicating Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 100kA Mounting Type Bolt Mount Package / Case Sectangular, Blade		
CategoryCircuit Protection Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating400AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.913" L x 2.402" W x 3.032" H (74.00mm x 61.00mm x 77.00mm)	Manufacturer Part Number	170M5742
Bit of the sector of the sec	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating400AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseSecangular, BladeSize / Dimension2.913" L x 2.402" W x 3.032" H (74.00mm x 77.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareCurrent Rating400AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated VoltageBolt MountMounting TypeBolt MountPackage / CaseRectangulan, BladeSize / Dimension2.913" L x 2.402" W x 3.032" H (74.00mm x 61.00mm x 77.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareFuse TypeSquareCurrent Rating400AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated VoltageBiol MountMounting TypeBolt MountPackage / CaseScangular, BladeSize / Dimension2.93" L x 2.402" W x 3.032" H (74.00mm x 67.00mm)	Package	Rectangular, Blade
Current Rating400AVoltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated VoltageBolt MountMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2,913" L x 2.402" W x 3.032" H (74.00mm x 61.00mm x 77.00mm)	Series	-
Voltage Rating - AC1300V (1.3kV)Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature100kABreaking Capacity @ Rated VoltageBolt MountMounting TypeBolt MountPackage / Case.2913" L x 2.402" W x 3.032" H (74.00mm x 61.00mm x 77.00mm)	Fuse Type	Square
Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Preaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangulang BaladeSize / Dimension2.913" L x 2.402" W x 3.032" H (74.00m x 77.00mm)	Current Rating	400A
Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.913" L x 2.402" W x 3.032" H (74.00mm x 61.00mm x 77.00mm)	Voltage Rating - AC	1300V (1.3kV)
ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.913" L x 2.402" W x 3.032" H (74.00mm x 61.00mm x 77.00mm)	Voltage Rating - DC	-
FeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.913" L x 2.402" W x 3.032" H (74.00mm x 61.00mm x 77.00mm)	Response Time	-
Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.913" L x 2.402" W x 3.032" H (74.00mm x 61.00mm x 77.00mm)	Applications	Electrical, Industrial
ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.913" L x 2.402" W x 3.032" H (74.00mm x 61.00mm x 77.00mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.913" L x 2.402" W x 3.032" H (74.00mm x 61.00mm x 77.00mm)	Class	-
Breaking Capacity @ Rated Voltage100kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.913" L x 2.402" W x 3.032" H (74.00mm x 61.00mm x 77.00mm)	Approvals	CSA, UR
Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.913" L x 2.402" W x 3.032" H (74.00mm x 61.00mm x 77.00mm)	Operating Temperature	-
Package / CaseRectangular, BladeSize / Dimension2.913" L x 2.402" W x 3.032" H (74.00mm x 61.00mm x 77.00mm)	Breaking Capacity @ Rated Voltage	100kA
Size / Dimension 2.913" L x 2.402" W x 3.032" H (74.00mm x 61.00mm x 77.00mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular, Blade
Report errors'	Size / Dimension	2.913" L x 2.402" W x 3.032" H (74.00mm x 61.00mm x 77.00mm)
		Report errors?

170M5742 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M5742, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com