

170M5887

170M5887 Information

Heisener.com	Part Number Manufacturer Category Description Package	170M5887 Eaton Circuit Protection Electrical, Specialty Fuses FUSE 500A 690V DIN 2 GR Rectangular, Blade
For Reference Only		For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



Request a Quote

170M5887 Specifications

Mandacturer Part NumberI70M5887MandacturerEatonCategoryCircuit ProtectionBelectrical, Specialty FusesPackageRectanguland BladeStriesSauaeFuse TypeSquareOurrent Rating-Voltage Rating + ACC-Voltage Rating + ACC-Specialty Fuses-String + ACC-Voltage Rating + ACC-Voltage Rating + ACC-Specialty Fuse-Applications-Specialty Fuses-Class-Approvals-Operating Fuse-Specialty Fuses-Munting Type-Munting Type-Specialty Class-Specialty Class- </th <th>_</th> <th></th>	_		
Carcial Protection Electrical, Specialty Fuses Package Rectangular, Blade Series * Fuse Type Square Fuse Type Square Current Rating - Voltage Rating - AC - Voltage Rating - DC - Applications - Applications - Parters - Approvals - Operating Temperature - Approvals - Mounting Type - Mounting Type - Package / Case - Ster / Dimension -	Manufacturer Part Number	170M5887	
FunctionElectrical, Specialty FusesPackageRectangular, BladeSeries*Fuse TypeSquareCurrent Rating-Voltage Rating - AC-Voltage Rating - DC-Response Time-Applications-Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2,671" L x 2,362" W x 2,913" H (68.00mm x 74.00mm)	Manufacturer	Eaton	
PackageRectangular, BladeSeries*Fuse TypeSquareCurren Rating-Voltage Rating - AC-Voltage Rating - DC-Response Time-Applications-Features-Class-Operating Temperature-Operating Capacity @ Rating - DC-Munting Type-Apploxable-Starking Capacity @ Rating - DC-Starking Capac	Category	Circuit Protection	
Series*Fuse TypeSquareCurrent Rating-Voltage Rating - AC-Voltage Rating - DC-Response Time-Applications-Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Houring Type-Package / CaseRectanguale BaleSize / Dimension-Size / Dimension		Electrical, Specialty Fuses	
States Second Seco	Package	Rectangular, Blade	
Current Rating-Voltage Rating - ACC-Voltage Rating - DCC-Response Time-Applications-Features-Class-Operating Temperature-Preaking Capacity @ Rated Voltage-Nourting Type-Package / Case-Size / Dimension-Size / Di	Series	*	
Voltage Rating - AC-Voltage Rating - DC-Response Time-Applications-Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseRectangulated BalageSize / Dimension2.671" L x 2.362" W x 2.913" H (68.00mm x 74.00mm)	Fuse Type	Square	
Voltage Rating - DC-Response Time-Applications-Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseRectangulated SealingSize / Dimension2.671"L x 2.362"W x 2.913"H (68.00mm x 74.00mm)	Current Rating	-	
Response Time-Applications-Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension267" L x 2.362" W x 2.913" H (68.00mm x 74.00mm)	Voltage Rating - AC	-	
Applications-Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2,671" L x 2,913" H (68,00mm x 74,00mm)	Voltage Rating - DC	-	
Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseRectangulare, BladeSize / Dimension2,671° L x 2,913° H (68.00mm x 74.00mm x 74	Response Time	-	
Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.671" L x 2.913" H (68.00mm x 74.00mm)	Applications	-	
Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.677" L x 2.362" W x 2.913" H (68.00mm x 74.00mm)	Features	-	
Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.677" L x 2.362" W x 2.913" H (68.00mm x 74.00mm)	Class	-	
Breaking Capacity @ Rated Voltage-Mounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.677" L x 2.362" W x 2.913" H (68.00mm x 74.00mm)	Approvals	-	
Mounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.677" L x 2.362" W x 2.913" H (68.00mm x 60.00mm x 74.00mm)	Operating Temperature	-	
Package / CaseRectangular, BladeSize / Dimension2.677" L x 2.362" W x 2.913" H (68.00mm x 60.00mm x 74.00mm)	Breaking Capacity @ Rated Voltage	-	
Size / Dimension 2.677" L x 2.362" W x 2.913" H (68.00mm x 60.00mm x 74.00mm)	Mounting Type	Holder	
	Package / Case	Rectangular, Blade	
Report errors?	Size / Dimension	2.677" L x 2.362" W x 2.913" H (68.00mm x 60.00mm x 74.00mm)	
		Report errors?	

170M5887 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M5887, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com