

170M5982

170M5982 Information

Heisener.com Gittal Write Land Terr	Part Number Manufacturer Category Description Package	170M5982 Eaton Circuit Protection Electrical, Specialty Fuses FUSE 315A 1000V 2TN/110 AR UR Rectangular, Blade For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



170M5982 Specifications

Manufacturer Part NumberI70M5982ManufacturerEatonCategoryCircuit ProtectionBelectrical, Specialty FusesPackageRectangular, BladeSeriesSquareFuse TypeSquareCurrent Rating-Voltage Rating + AC-Voltage Rating + AC-Sponse Time-Applications-Class-Approvals-Operating Temperature-Operating Temperature-Approvals-Applications Quality Back-Approvals-Approvals-Approvals-Autoning TypeBot MountAutoning TypeSciangula BladeSiz / Dimension-Siz / Dimension-Siz / Dimension-Autoning Type-Siz / Dimension-Autoning Type-Siz / Dimension-Autoning Type-Autoning Type		
CategoryCircuit Protection Electrical, Specialty FusesPackageRectangular, BladeSeries*Fuse TypeSquareFuse TypeSquareCurrent Rating-Voltage Rating - AC-Voltage Rating - DC-Applications-Features-Clars-Approvals-Operating Temperature-Operating Capacity @ Rating Action-Applications-Features-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeBolt MountPackage / CaseSctongular, BladeSize / Dimension150° L x 2.32° W x 2.950° H (80.00mm x 59.00mm	Manufacturer Part Number	170M5982
PackageElectrical, Specialty FusesPackageRectangular, BladeSeries*Fuse TypeSquareCurrent Rating-Voltage Rating - AC-Voltage Rating - DC-Response Time-Applications-Features-Class-Operating Temperature-Derating Capacity @ Rated Voltage-Breaking Capacity @ Rated Voltage-Mounting TypeBolt MountPackage / CaseSi150" L x 2.323" W x 2.953" H (80.00mm x 59.00mm x 75.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries*Fuse TypeSquareCurrent Rating-Voltage Rating - AC-Voltage Rating - DC-Response Time-Applications-Features-Class-Operating Temperature-Derating Capacity @ Rated Voltage-Mounting Type-Package / CaseSctangular, BladeSize / DimensionStol "L x 2,323" W x 2,953" H (80.00mm x 75.00mm)	Category	Circuit Protection
Series*Fuse TypeSquareCurrent Rating-Voltage Rating - AC-Voltage Rating - DC-Response Time-Applications-Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeBolt MountPackage / CaseScot Sulf and BalageSize / Dimension3.150" Lx 2.323" W x 2.953" H (80.00mm x 55.00mm)		Electrical, Specialty Fuses
Sectors Sequeree Fuse Type Squaree Fuse Type Squaree Current Rating - Voltage Rating - AC - Voltage Rating - DC - Response Time - Applications - Features - Class - Approvals - Operating Temperature - Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 3.150" L x 2.323" W x 2.953" H (80.00mm x 59.00mm x 75.00mm)	Package	Rectangular, Blade
Current Rating-Voltage Rating - AC-Voltage Rating - DC-Response Time-Applications-Applications-Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Hounting TypeBit MountPackage / Casa-Size / Dimension-Size / Dimensi	Series	*
Voltage Rating - AC-Voltage Rating - DC-Response Time-Applications-Applications-Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeBolt MountPackage / CaseRectangulandeSize / Dimension3.150" L x 2.323" W x 2.953" H (80.00mm x 75.00mm x 75.00mm)	Fuse Type	Square
Voltage Rating - DC-Response Time-Applications-Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeBolt MountPackage / CaseRectangulandeSize / Dimension3.150" L x 2.323" W x 2.953" H (80.0000 m x 7.5000	Current Rating	-
Response Time-Applications-Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.323" W x 2.953" H (80.00mm x 59.00mm x 75.00mm)	Voltage Rating - AC	-
Applications-Applications-Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.323" W x 2.953" H (80.00m x 59.00m x 75.00m m)	Voltage Rating - DC	-
Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.323" W x 2.953" H (80.000m x 75.000m	Response Time	-
Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.323" W x 2.953" H (80.00m x 59.00m x 75.00m m)	Applications	-
Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.323" W x 2.953" H (80.00mm x 75.00mm)	Features	-
Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.323" W x 2.953" H (80.00mm x 59.00mm x 75.00mm)	Class	-
Breaking Capacity @ Rated Voltage-Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.323" W x 2.953" H (80.00mm x 59.00mm x 75.00mm)	Approvals	-
Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.323" W x 2.953" H (80.00mm x 59.00mm x 75.00mm)	Operating Temperature	-
Package / CaseRectangular, BladeSize / Dimension3.150" L x 2.323" W x 2.953" H (80.00mm x 59.00mm x 75.00mm)	Breaking Capacity @ Rated Voltage	-
Size / Dimension 3.150" L x 2.323" W x 2.953" H (80.00mm x 59.00mm x 75.00mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	3.150" L x 2.323" W x 2.953" H (80.00mm x 59.00mm x 75.00mm)
		Report errors?

170M5982 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M5982, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com