

170M5986

170M5986 Information

| Heisener.com | Part Number | 170M5986 |
|--------------------|--------------|---|
| | Manufacturer | Eaton |
| | Category | Circuit Protection Electrical, Specialty Fuses |
| | Description | FUSE 500A 1000V 2TN/110 AR UR |
| | Package | Rectangular, Blade |
| | | For the pricing/inventory/lead time, please contact |
| For Reference Only | | us Website: https://www.heisener.com E-mail: salesdept@heisener.com |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



Request a Quote

170M5986 Specifications

| Series*Fuse TypeSquareCurrent Rating-Voltage Rating - AC-Voltage Rating - DC-Response Time-Applications-Features-Class-Approvals-Approvals-Approvals-Conserting-Approvals-Ap | _ | | |
|---|-----------------------------------|--|--|
| CategoryCircuit Protection Electrical, Specialty FusesPackageRectangular, BladeSeries*Fuse TypeSquareFuse TypeSquareCurren Rating-Voltage Rating - AC-Voltage Rating - DC-Applications-Fuser Type-Carsen Time-Applications-Pactange Super Supe | Manufacturer Part Number | 170M5986 | |
| Electrical, Specialty FusesPackageRectangular, BladeSeries*Fuse TypeSquareCurrent Rating-Voltage Rating - AC-Voltage Rating - DC-Response Time-Applications-Features-Class-Operating Temperature-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.323" W x 2.953" H (80.00mm x 55.00mm x 75.00mm) | Manufacturer | Eaton | |
| PackageRectangular, BladeSeries*Fuse TypeSquareCurrent Rating-Voltage Rating - AC-Voltage Rating - DC-Response Time-Applications-Features-Class-Operating Temperature-Operating Capacity @ Rated Voltage-Mounting Type-Package / CaseSolt MountSize / DimensionSito" L x 2,323" W x 2,953" H (80.00mm x 75.00mm) | Category | Circuit Protection | |
| Series*Fuse TypeSquareCurrent Rating-Voltage Rating - AC-Voltage Rating - DC-Response Time-Applications-Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeBolt MountPackage / CaseStor "L x 2.323" W x 2.953" H (80.00mm x 59.00mm x 75.00mm) | | Electrical, Specialty Fuses | |
| Striks Square Fuse Type Square Current Rating - Voltage Rating - AC - Voltage Rating - DC - Response Time - Applications - Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage - Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 3.150" L x 2.323" W x 2.953" H (80.00mm x 59.00mm x 75.00mm) | Package | Rectangular, Blade | |
| Current Rating-Voltage Rating - AC-Voltage Rating - DC-Response Time-Applications-Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting Type-Package / Case-Size / Dimension-Size / Dimension </td <td>Series</td> <td colspan="2">*</td> | Series | * | |
| Voltage Rating - AC-Voltage Rating - DC-Response Time-Applications-Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeBolt MountPackage / CaseRectangulaneSize / Dimension3.150" L x 2.323" W x 2.953" H (80.00mm x 75.00mm) | Fuse Type | Square | |
| Voltage Rating - DC-Response Time-Applications-Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Nounting TypeBolt MountPackage / CaseRectangular BladeSize / Dimension3.150" L x 2.323" W x 2.953" H (80.00m x 75.00mm) | Current Rating | - | |
| Response Time-Applications-Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.323" W x 2.953" H (80.00m x 59.00m x 75.00mm) | Voltage Rating - AC | - | |
| Applications-Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.923" H (80.00mm x 59.00mm x 75.00mm) | Voltage Rating - DC | - | |
| Features-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.953" H (80.00mm x 59.00mm x 75.00mm) | Response Time | - | |
| Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.323" W x 2.953" H (80.00mm x 75.00mm) | Applications | - | |
| Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.323" W x 2.953" H (80.00mm x 75.00mm) | Features | - | |
| Operating Temperature-Breaking Capacity @ Rated Voltage-Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.323" W x 2.953" H (80.00mm x 59.00mm x 75.00mm) | Class | - | |
| Breaking Capacity @ Rated Voltage-Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.323" W x 2.953" H (80.00mm x 59.00mm x 75.00mm) | Approvals | - | |
| Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension3.150" L x 2.323" W x 2.953" H (80.00mm x 59.00mm x 75.00mm) | Operating Temperature | - | |
| Package / CaseRectangular, BladeSize / Dimension3.150" L x 2.323" W x 2.953" H (80.00mm x 59.00mm x 75.00mm) | Breaking Capacity @ Rated Voltage | - | |
| Size / Dimension 3.150" L x 2.323" W x 2.953" H (80.00mm x 59.00mm x 75.00mm) | Mounting Type | Bolt Mount | |
| | Package / Case | Rectangular, Blade | |
| Report errors? | Size / Dimension | 3.150" L x 2.323" W x 2.953" H (80.00mm x 59.00mm x 75.00mm) | |
| | | Report errors? | |

170M5986 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M5986, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com