

170M6168

170M6168 Information



For Reference Only

| Part Number | 170M6168 | |
|--------------|--|--|
| Manufacturer | Eaton | |
| Category | Circuit Protection Electrical, Specialty Fuses | |
| Description | FUSE SQ 1.5KA 700VAC RECTANGULAR | |
| Package | Rectangular, Blade | |
| | For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com | |



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



170M6168 Specifications

| Manufacturer Part NumberI70M6168ManufacturerEatonCategoryCircuit ProtectionElectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating1.5kAVoltage Rating - ACC700VVoltage Rating - DC-ApplicationsElectrical, IndustrialFaturesIndicatingClass-ApprovalsCE, CSA, UROperating TypeSold MountMounting TypeBolt MountPackage / CaseRectangular, BladeSize / DimensionSoloss' Type / Schaft MountSize / DimensionSoloss' Type / Schaft MountSize / DimensionSoloss' Type / Schaft MountSize / DimensionSoloss' Type / Schaft Moltont | | |
|--|-----------------------------------|--|
| CategoryCircuit ProtectionBectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareFuse TypeSquareCurrent Rating1.5kAVoltage Rating - AC700VVoltage Rating - DC-ApplicationsElectrical, IndustrialApplicationsElectrical, IndustrialFaturesIndicatingOperating Temperature-ApprovalsCE, CSA, UROperating Capacity @ Rated Voltage300kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2,008" Lx 2.992" Wx 3.543" H (51.00mmx 90.00mm) | Manufacturer Part Number | 170M6168 |
| First of the section | Manufacturer | Eaton |
| PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating1.5kAVoltage Rating - AC700VVoltage Rating - DC-Applications-Response Time-FeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Apackage / CaseSold Administry BoltResponse Type-Starting Capacity @ Rated Wolts-Starting Type-Starting Type- </td <td>Category</td> <td>Circuit Protection</td> | Category | Circuit Protection |
| Series-Fuse TypeSquareCurrent Rating1.5kAVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature200kAMounting TypeBolt MountPackage / CaseRectangulandeSize / Dimension2008" L x 2.992" W x 3.543" H (51.00mm x 90.00mm) | | Electrical, Specialty Fuses |
| Fuse Type Square Fuse Type Square Fuse Type Square Current Rating 1.5kA Voltage Rating - AC 700V Voltage Rating - DC - Response Time - Applications Electrical Industrial Features Indicating Class - Approvals ElectroAL UR Operating Temperature - Breaking Capacity @ Rated Voltage OlokA Mounting Type Bolt Mount Package / Case Scots" L x 2.992" W x 3.543" H (51.00mm x 90.00mm) | Package | Rectangular, Blade |
| Current Rating1.5kAVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / Case.Size / Dimension2.008" L x 2.992" W x 3.543" H (51.00mm x 76.00mm x 90.00mm) | Series | - |
| Voltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated VoltageBolt MountPackage / CaseRectangulaneSize / Dimension2008" L x 2.992" W x 3.543" H (51.00mm x 90.00mm) | Fuse Type | Square |
| Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.543" H (51.00mm x 76.00mm x 90.00mm) | Current Rating | 1.5kA |
| Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.543" H (51.00mm x 76.00mm x 90.00mm) | Voltage Rating - AC | 700V |
| ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2,008" L x 2,992" W x 3,543" H (51,00mm x 76,00mm x 90,00mm) | Voltage Rating - DC | - |
| FeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.543" H (51.00mm x 76.00mm x 90.00mm) | Response Time | - |
| Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.543" H (51.00mm x 76.00mm x 90.00mm) | Applications | Electrical, Industrial |
| ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.543" H (51.00mm x 76.00mm x 90.00mm) | Features | Indicating |
| Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.543" H (51.00mm x 76.00mm x 90.00mm) | Class | - |
| Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.543" H (51.00mm x 76.00mm x 90.00mm) | Approvals | CE, CSA, UR |
| Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.543" H (51.00mm x 76.00mm x 90.00mm) | Operating Temperature | - |
| Package / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.543" H (51.00mm x 76.00mm x 90.00mm) | Breaking Capacity @ Rated Voltage | 200kA |
| Size / Dimension 2.008" L x 2.992" W x 3.543" H (51.00mm x 76.00mm x 90.00mm) | Mounting Type | Bolt Mount |
| | Package / Case | Rectangular, Blade |
| Report errors | Size / Dimension | 2.008" L x 2.992" W x 3.543" H (51.00mm x 76.00mm x 90.00mm) |
| | | Report errors? |

170M6168 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M6168, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com