

170M6170

170M6170 Information



For Reference Only

Part Number	170M6170	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE SQ 1.8KA 700VAC RECTANGULAR	
Package	Rectangular, Blade	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



170M6170 Specifications

Manufacturer Part Number170M6170ManufacturerEatonCategoryCircuit ProtectionPackageRectangulary FusesPackageRectangulary BladeSeries-Fuse TypeSquareCurrent Rating1.8kAVoltage Rating - DC-Voltage Rating - DC-ApplicationsElectrical, IndustrialApprovalsElectrical, IndustrialClass-ApprovalsCirc SA, UROperating Temperature-ApprovalsCirc SA, URMouning TypeBit MountPackage / CaseScoles La Sa, Sa, Sa, Sa, Sa, Sa, Sa, Sa, Sa, Sa		
CategoryCircuit Protection Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareFuse TypeSquareCurrent Rating1.8kAVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFaturesIndicatingApprovalsCE, CSA, UROperating Temperature-Preaking Capacity @ Rated Voltage200kAMounting TypeBiol MountPackage / CaseRectangular, BladeSize / Dimension2.00% X 2.092" W x 3.543" H (51.00mm x 76.00mm)	Manufacturer Part Number	170M6170
Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating1.8kAVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature200kABreaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2008" L x 2.992" W x 3.543" H (51.00mm x 76.00mm x 90.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating1.8kAVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating TemperatureSoukAMounting TypeBolt MountPackage / CaseRectangulage BladeSize / Dimension2.008" L x 2.992" W x 3.543" H (51.00mm x 90.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareCurrent Rating1.8kAVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature200kABreaking Capacity @ Rated VoltageBolt MountPackage / CaseRectangulan, BladeSize / Dimension2.008" L x 2.992" W x 3.543" H (51.00mm x 90.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareFuse TypeSquareCurrent Rating1.8kAVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature200kAFeaking Capacity @ Rated VoltageSolt Mounting TypePackage / CaseRectangulandeSize / Dimension2.008" L x 2.992" W x 3.543" H (51.00mm x 90.00mm)	Package	Rectangular, Blade
Curren Rating1.8kAVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature00kAFeaturesSol MountApontong TypeBid MountPackage / CaseScol MountSize / Dimension2008" L x 2.992" W x 3.543" H (51.00mm x 90.00mm)	Series	-
Notage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated VoltageBolt MountMounting TypeBolt MountPackage / Case.Size / Dimension2.008" L x 2.992" W x 3.543" H (51.00mm x 90.00mm)	Fuse Type	Square
Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.543" H (51.00mm x 76.00mm x 90.00mm)	Current Rating	1.8kA
Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2,008" L x 2,992" W x 3,543" H (51,00m x 90,00m m)	Voltage Rating - AC	700V
ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2,008" L x 2,992" W x 3,543" H (51,00mm x 76,00mm x 90,00mm)	Voltage Rating - DC	-
FeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2,008" L x 2,992" W x 3,543" H (51,00m x 76,00m x 90,00m x 90,00	Response Time	-
Class-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.543" H (51.00mm x 76.00mm x 90.00mm)	Applications	Electrical, Industrial
ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2,008" L x 2.992" W x 3.543" H (51.00mm x 76.00mm x 90.00mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.543" H (51.00mm x 76.00mm x 90.00mm)	Class	-
Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.543" H (51.00mm x 76.00mm x 90.00mm)	Approvals	CE, CSA, UR
Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.543" H (51.00mm x 76.00mm x 90.00mm)	Operating Temperature	-
Package / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.543" H (51.00mm x 76.00mm x 90.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 2.008" L x 2.992" W x 3.543" H (51.00mm x 76.00mm x 90.00mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	2.008" L x 2.992" W x 3.543" H (51.00mm x 76.00mm x 90.00mm)
		Report errors?

170M6170 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M6170, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com