

170M6212

170M6212 Information



For Reference Only

Part Number	170M6212	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE SQ 800A 700VAC RECTANGULAR	
Package	Rectangular, Blade	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



170M6212 Specifications

Manufacturer Part Number170M6212ManufacturerEatonCategoryCircuit ProtectionPackageRectanglary FusesPackageRectangulary BladeSeries-Fuse TypeSquareOurren RatingS00AVoltage Rating - DC-Voltage Rating - DC-Sprose Time-ApplicationsElectrical, IndustrialCarsen Same-Approvals-Ourant Rating-Seating - DC-Stating - DC-Sprose Time-ApplicationsElectrical, IndustrialClass-Approvals-Operating Temperature-Operating Temperature-Munting TypeBit MountPackage / Case-Siz / Dimension-Siz / Dimension- <td< th=""><th></th><th></th></td<>		
CategoryCircuit Protection Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareFuse TypeSquareCurrent Rating800AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Standard Standard Standard Standard StandardMounting TypeSold MountPackage / CaseRectangular, BladeSiz / DimensionStonger Yw 3, Stal" H (51.00mm x 76.00mm)	Manufacturer Part Number	170M6212
Field of the section	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating800AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating TemperatureSolokAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.543" H (51.00mm x 76.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareCurrent Rating800AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature200kABreaking Capacity @ Rated VoltageBolt MountiPackage / CaseRectangulang BaleSize / Dimension2,008" L x 2,992" W x 3,543" H (51.00mm x 96.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareFuse TypeSquareCurrent RatingS00AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature200KAFeaking Capacity @ Rated VoltageSolt Mounting TypePackage / CaseRectangulane BalaneSize / Dimension2008" L x 2.992" W x 3.543" H (51.00mm x 90.00mm)	Package	Rectangular, Blade
Current RatingSOAVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Beaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseScow BallageSize / Dimension2,008" L x 2,992" W x 3,543" H (51,00mm x 90,00mm)	Series	-
Voltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated VoltageBolt MountMounting TypeBolt MountPackage / CaseRectangulandeSize / Dimension2.008" L x 2.992" W x 3.543" H (51.00mm x 90.00mm)	Fuse Type	Square
Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage00kAMounting TypeBolt MountPackage / CaseRectangulandeSize / Dimension2.008" L x 2.992" W x 3.543" H (51.00mm x 90.00mm)	Current Rating	800A
Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2,008" L x 2,992" W x 3,543" H (51,00mm x 90,00mm)	Voltage Rating - AC	700V
ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2,008" L x 2,992" W x 3,543" H (51,00mm x 76,00mm x 90,00mm)	Voltage Rating - DC	-
FeaturesIndicatingFeaturesIndicatingClass-ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.543" H (51.00mm x 76.00mm x 90.00mm)	Response Time	-
Class - Approvals CE, CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Rectangular, Blade Size / Dimension 2.008" L x 2.992" W x 3.543" H (51.00mm x 76.00mm x 90.00mm)	Applications	Electrical, Industrial
ApprovalsCE, CSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.543" H (51.00mm x 76.00mm x 90.00mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.543" H (51.00mm x 76.00mm x 90.00mm)	Class	-
Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.543" H (51.00mm x 76.00mm x 90.00mm)	Approvals	CE, CSA, UR
Mounting TypeBolt MountPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.543" H (51.00mm x 76.00mm x 90.00mm)	Operating Temperature	-
Package / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.543" H (51.00mm x 76.00mm x 90.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 2.008" L x 2.992" W x 3.543" H (51.00mm x 76.00mm x 90.00mm)	Mounting Type	Bolt Mount
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	2.008" L x 2.992" W x 3.543" H (51.00mm x 76.00mm x 90.00mm)
		Report errors?

170M6212 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M6212, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com