

170M6415

170M6415 Information



Part Number	170M6415	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE SQUARE 1.1KA 700VAC	
Package	Rectangular, Blade	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



170M6415 Specifications

Manufacturer Part Number170M6415ManufacturerEatonCategoryCircuit ProtectionPackageRectanglary FusesPackageRectanglary BladeSeries-Fuse TypeSquareCurrent Rating1.kAVoltage Rating - DC-Voltage Rating - DC-Sprose Time-ApplicationsElectrical IndustrialClass-Approvals-Operating Temperature-Operating Temperature-Operating Temperature-Apploxals-Muning Type-Package / Case-Sprovel / Case-Operating Temperature-Muning Type-Sprovel / Case-Sprovel / Case- <th></th> <th></th>		
CategoryCircuit Protection Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareFuse TypeSquareCurren Rating1.1kAVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialKaterIndicatingVoltage Rating - Marce-ApplicationsElectrical, IndustrialFeaturesIndicatingOperating Temperature-ApprovalsCSA, UROperating Temperature200AMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2008" k 2.992" W s 3.652" H (51.00mm s 76.00mm s 92.00mm)	Manufacturer Part Number	170M6415
Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurren Rating1.1kAVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating1.1kAVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareCurrent Rating1.1kAVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature200kAMounting TypeBolderPackage / CaseRectangulang BalageSize / Dimension2.008" L x 2.992" W x 3.622" H (51.00mm x 92.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareFuse TypeSquareCurrent Rating1.1kAVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature20kAHourting TypeBiderPackage / CaseRectangulant BideSize / Dimension2.008" L x 2.992" W x 3.622" H (51.00mm x 92.00mm)	Package	Rectangular, Blade
Current RatingI.kAVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseScon guilt and guilt a	Series	-
Voltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage300kAMounting TypeHolderPackage / CaseRectangulandSize / Dimension2.008" L x 2.992" W x 3.622" H (51.00mm x 92.00mm)	Fuse Type	Square
Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage00kAMounting TypeHolderPackage / CaseRectangulandeSize / Dimension2.008" L x 2.992" W x 3.622" H (51.00mm x 92.00mm)	Current Rating	1.1kA
Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2,008" L x 2,992" W x 3,622" H (51,00m x 92,00m x 9	Voltage Rating - AC	700V
ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2,008" L x 2,992" W x 3,622" H (51,00mm x 76,00mm x 92,00mm)	Voltage Rating - DC	-
FeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage20kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2,008" L x 2,992" W x 3,652" H (51,00m x 76,00m x 92,00m x 92,00	Response Time	-
Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2,008" L x 2.992" W x 3.622" H (51.00mm x 92.00mm)	Applications	Electrical, Industrial
ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Class	-
Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Approvals	CSA, UR
Mounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Operating Temperature	-
Package / Case Rectangular, Blade Size / Dimension 2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Mounting Type	Holder
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)
		Report errors?

170M6415 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M6415, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com