

170M6419

170M6419 Information



Part Number	170M6419	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE SQUARE 1.6KA 700VAC	
Package	Rectangular, Blade	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



170M6419 Specifications

Manufacturer Part Number170M6419ManufacturerEatonCategoryCircuit ProtectionElectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating1.6kAVoltage Rating - AC700VVoltage Rating - DC-ApplicationsElectrical, IndustrialFeaturesIndustrialApprovalsCSA, UROperating Temperature-ApprovalsCSA, URMounting TypeBoldeMounting TypeSove TanguageStarey Case200kAStarey CaseSove TanguageStarey CaseSove TanguageSta		
CategoryCircuit ProtectionRectarcal, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareFuse TypeSquareCurrent Rating1.6kAVoltage Rating - AC700VVoltage Rating - DC-ApplicationsEctercial, IndustrialFeaturesIndicatingApplorationsEctercial, IndustrialClass-ApprovalsSA, UROperating TemperatureSou AApontage Rated VoltageSou AMounting TypeSou AAutoning TypeSou AFackage / CaseScangular, BladeSize / DimensionSous T, Sa, Sa, Sa, Sa, Sa, Sa, Sa, Sa, Sa, Sa	Manufacturer Part Number	170M6419
PackageElectrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating1.6kAVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating1.6kAVoltage Rating - AC700VVoltage Rating - DC-ApplicationsElectrical, IndustrialApplications.Class-ApprovalsCSA, UROperating Temperature.Breaking Capacity @ Rated Voltage.Mounting Type.Package / Case.Size / Dimension.Size / Dimension	Category	Circuit Protection
Series-Fuse TypeSquareFuse TypeSquareCurrent Rating1.6kAVoltage Rating - AC700VVoltage Rating - DC-Aesponse Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeRectangulang BalagePackage / CaseScongulang BalageSize / Dimension2.008" L x 2.992" W x 3.622" H (51.00mm x 92.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareFuse TypeSquareCurrent Rating1.6kAVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature300AFeatures200AMounting TypeHolderPackage / CaseScangular, BladeSize / Dimension2.008" L x 2.992" W x 3.622" H (51.00mm x 92.00mm)	Package	Rectangular, Blade
Current RatingI.6kAVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature200kABreaking Capacity @ Rated VoltageHolderPackage / CaseRectangulandSize / Dimension2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Series	-
Voltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage600kAMounting TypeHolderPackage / CaseScongular, BladeSize / Dimension2,008" L x 2,992" W x 3,622" H (51,00mm x 92,00mm)	Fuse Type	Square
Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangulandeSize / Dimension2,008" L x 2,992" W x 3,6322" H (51,00m x 9,00m	Current Rating	1.6kA
Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.622" H (51.00m x 92.00mm)	Voltage Rating - AC	700V
ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangulandSize / Dimension2,008" L x 2,992" W x 3,652" H (51,00m x 76,00m x 92,00m x 92,	Voltage Rating - DC	-
FeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangulandSize / Dimension2,008" L x 2,902" W x 3,652" H (5,000 m x 7,600 m x	Response Time	-
Class-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.622" H (51.00m x 76.00m x 92.00m x 92.0	Applications	Electrical, Industrial
ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.622" H (51.00mm x 92.00mm)	Features	Indicating
Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Class	-
Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Approvals	CSA, UR
Mounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Operating Temperature	-
Package / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Mounting Type	Holder
	Package / Case	Rectangular, Blade
Deport amor	Size / Dimension	2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)
Kepon enor		Report errors?

170M6419 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M6419, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com