

170M6513 Information



For Reference Only

Part Number 170M6513 Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE SQUARE 900A 700VAC

Package Rectangular, Blade

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









170M6513 Specifications

Manufacturer Part Number 170M6513 Manufacturer Eaton Category Circuit Protection Package Rectangular, Blade Series - Fuse Type Square Current Rating 900A Voltage Rating - AC 700V Voltage Rating - DC - Response Time - Applications Electrical, Industrial Features Indicating Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm) Report errors?		
Category Circuit Protection Electrical, Specialty Fuses Package Rectangular, Blade Series - Fuse Type Square Current Rating 900A Voltage Rating - AC 700V Voltage Rating - DC - Response Time - Applications Electrical, Industrial Features Indicating Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Manufacturer Part Number	170M6513
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating900AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Manufacturer	Eaton
Package Rectangular, Blade Series - Fuse Type Square Current Rating 900A Voltage Rating - AC 700V Voltage Rating - DC - Response Time - Applications Electrical, Industrial Features Indicating Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Category	Circuit Protection
Series - Fuse Type Square Current Rating 900A Voltage Rating - AC 700V Voltage Rating - DC - Response Time - Applications Electrical, Industrial Features Indicating Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareCurrent Rating900AVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCSA, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Package	Rectangular, Blade
Current Rating 900A Voltage Rating - AC 700V Voltage Rating - DC - Response Time - Applications Electrical, Industrial Features Indicating Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2008	Series	-
Voltage Rating - AC Voltage Rating - DC Response Time Applications Electrical, Industrial Indicating Class Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 700V 700V 700V 700V 600V Flexible Size / Dimension Foods Flexible Size / Dimension Flexi	Fuse Type	Square
Voltage Rating - DC Response Time - Applications Electrical, Industrial Features Indicating Class - Approvals CSA, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension	Current Rating	900A
Response Time Applications Electrical, Industrial Features Indicating Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension - Electrical, Industrial Industrial CSA, UR - CSA, UR - Breaking Capacity @ Rated Voltage Approvals - Breaking Capacity @ Rated Voltage - Breakin	Voltage Rating - AC	700V
Applications Electrical, Industrial Features Indicating Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Voltage Rating - DC	-
Features Indicating Class - Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Response Time	-
Class - CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Applications	Electrical, Industrial
Approvals CSA, UR Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension CSA, UR - - - 200kA Holder Rectangular, Blade 2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Features	Indicating
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Approvals	CSA, UR
Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Operating Temperature	-
Package / Case Rectangular, Blade Size / Dimension 2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)	Mounting Type	Holder
	Package / Case	Rectangular, Blade
Report errors?	Size / Dimension	2.008" L x 2.992" W x 3.622" H (51.00mm x 76.00mm x 92.00mm)
		Report errors?

170M6513 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

170M6513 Payment Methods



















170M6513 Shipping Methods













If you have any question about 170M6513, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com