

170M6814D


Request a Quote

170M6814D Information



For Reference Only

Part Number	170M6814D	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE SQ 1KA 700VAC RECTANGULAR	
Package	Rectangular, Blade	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



170M6814D Specifications

ManufacturerEatonCategoryCircuit ProtectionElectrical, Specialty FusesPackageRectangular, BladeSeries-SeriesGuareCurrent RatingKAVoltage Rating - AC700VVoltage Rating - DC-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseSectangular, BladeSize / Dimension2,677" L x 2.992" W x 3.465" H (68.00mm x 76.00mm x 88.00mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackageRectangular, BladeSeries-Fuse TypeSquareCurrent RatingIkAVoltage Rating - AC700VVoltage Rating - DC-ApplicationsElectrical, IndustrialApplicationsElectrical, IndustrialClass-ApprovalsCE, UROperating Temperature200kABreaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.677" L x 2.992" W x 3.465" H (68.00mm x 76.00mm x 88.00mm)	Manufacturer Part Number	170M6814D
Bit of J Electrical, Specialty Fuses Package Rectangular, Blade Series - Fuse Type Square Current Rating IkA Voltage Rating - AC 700V Voltage Rating - DC - Response Time - Applications Electrical, Industrial Features Indicating Class - Approvals CE, UR Operating Temperature 200kA Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2677" L x 2.992" W x 3.465" H (68.00mm x 76.00mm x 88.00mm)	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent RatingIkAVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, UROperating Type200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.677" L x 2.992" W x 3.465" H (68.00mn x 76.00mn x 88.00mm)	Category	Circuit Protection
Series-Fuse TypeSquareCurrent RatingIkAVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.671" L x 2.992" W x 3.465" H (68.00mm x 76.00mm x 88.00mm)		Electrical, Specialty Fuses
Fuse TypeSquareFuse TypeSquareCurrent RatingIkAVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangulang BaldeSte / Dimension2671" L x 2.992" W x 3.465" H (68.00mm x 76.00mm x 88.00mm)	Package	Rectangular, Blade
Current RatingIkAVoltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.677" L x 2.992" W x 3.465" H (68.00mm x 76.00mm x 88.00mm)	Series	-
Voltage Rating - AC700VVoltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.671" L x 2.992" W x 3.465" H (68.00mm x 76.00mm x 88.00mm)	Fuse Type	Square
Voltage Rating - DC-Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.677" L x 2.992" W x 3.465" H (68.00mm x 76.00mm x 88.00mm)	Current Rating	1kA
Response Time-ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2,677" L x 2.992" W x 3.465" H (68.00mm x 76.00mm x 88.00mm)	Voltage Rating - AC	700V
ApplicationsElectrical, IndustrialFeaturesIndicatingClass-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.677" L x 2.992" W x 3.465" H (68.00mm x 76.00mm x 88.00mm)	Voltage Rating - DC	-
FeaturesIndicatingClass-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.677" L x 2.992" W x 3.465" H (68.00mm x 76.00mm x 88.00mm)	Response Time	-
Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.677" L x 2.992" W x 3.465" H (68.00mm x 76.00mm x 88.00mm)	Applications	Electrical, Industrial
ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.677" L x 2.992" W x 3.465" H (68.00mm x 76.00mm x 88.00mm)	Features	Indicating
AAOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.677" L x 2.992" W x 3.465" H (68.00mm x 76.00mm x 88.00mm)	Class	-
Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.677" L x 2.992" W x 3.465" H (68.00mm x 76.00mm x 88.00mm)	Approvals	CE, UR
Mounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.677" L x 2.992" W x 3.465" H (68.00mm x 76.00mm x 88.00mm)	Operating Temperature	-
Package / CaseRectangular, BladeSize / Dimension2.677" L x 2.992" W x 3.465" H (68.00mm x 76.00mm x 88.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 2.677" L x 2.992" W x 3.465" H (68.00mm x 76.00mm x 88.00mm)	Mounting Type	Holder
	Package / Case	Rectangular, Blade
Report errors'	Size / Dimension	2.677" L x 2.992" W x 3.465" H (68.00mm x 76.00mm x 88.00mm)
		Report errors?

170M6814D Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE GUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 170M6814D, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com