

171684J400Q-F

171684J400Q-F Information

www.heisener.com	171684J400Q-F Cornell Dubilier Electronics (CDE) Capacitors Film Capacitors CAP FILM 0.68UF 5% 400VDC RADIAL Radial For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



171684J400Q-F Specifications

ManufacturerCornell Dublier Electronics (CDE)CategoryCapacitorsFilm CapacitorsFilm CapacitorsPackageRadialSeries171Capacitance0.68µFTolerance±5%Voltage Rating - AC200VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedSeries Resistance)30 mOhmOperating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.260° L x 0.512° W (32.00mm x 13.00mm)Height - Seated (Max)0.886° (22.50mm)TerminationPC PinsLead Spacing1.083° (27.50mm)ApplicationsHigh Pulse, DV/DTFeatures-		
CategoryCapacitorsPackageRadialPackageRadialSeries171Capacitance0.68µFTolerance±5%Voltage Rating - AC220VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedDoprating Temperature.55°C ~ 105°CMouning TypeThrough HolePackage / CaseRadialSize / Dimension1.260° L x 0.512° W (32.00mm x 13.00mm)Height - Seated (Max)0.886° (22.50mm)Lead Spacing1.083° (27.50mm)ApplicationsHigh Pulse, DV/DTFeatures.	Manufacturer Part Number	171684J400Q-F
Film CapacitorsPackageRadialSeries171Capacitance0.68µFTolerance±5%Voltage Rating - AC220VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)30 mOhmOperating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.260° L x 0.512° W (32.00mm x 13.00mm)Height - Seated (Max)0.886° (22.50mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsHigh Pulse, DV/DTFeatures-	Manufacturer	Cornell Dubilier Electronics (CDE)
PackageRadialSeries171Capacitance0.68µFTolerance±5%Voltage Rating - AC220VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)30 mOhmOperating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.260" L x 0.512" W (32.00mm x 13.00mm)Height - Seated (Max)0.886" (22.50mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsHigh Pulse, DV/DTFeatures-	Category	Capacitors
Series I1 Capacitance 0.68µF Tolerance ±5% Voltage Rating - AC 220V Voltage Rating - DC 400V Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) 30 mOhm Operating Temperature -55°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dimension 1.260" L x 0.512" W (32.00mm x 13.00mm) Height - Seated (Max) 0.886" (22.50mm) Termination PC Pins Lead Spacing 1.083" (27.50mm) Applications High Pulse, DV/DT Features -		Film Capacitors
Capacitance0.68µFTolerance±5%Voltage Rating - AC220VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)30 mOhmOperating Temperature-55°C ~ 105°CMounting TypeRadialPackage / CaseRadialSize / Dimension1.260" L x 0.512" W (32.00mm x 13.00mm)Height - Seated (Max)0.886" (22.50mm)Lead Spacing1.083" (27.50mm)ApplicationsHigh Pulse, DV/DTFeatures-	Package	Radial
Tolerance±5%Voltage Rating - AC220VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)30 mOhmOperating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.260° L x 0.512″ W (32.00mm x 13.00mm)Height - Seated (Max)0.886° (22.50mm)TerminationPC PinsLead Spacing1.083″ (27.50mm)ApplicationsHigh Pulse, DV/DTFeatures-	Series	171
Voltage Rating - AC220VVoltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)30 mOhmOperating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.260" L x 0.512" W (32.00mm x 13.00mm)Height - Seated (Max)0.886" (22.50mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsHigh Pulse, DV/DTFeatures-	Capacitance	0.68µF
Voltage Rating - DC400VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)30 mOhmOperating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.260" L x 0.512" W (32.00mm x 13.00mm)Height - Seated (Max)0.886" (22.50mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsHigh Pulse, DV/DTFeatures-	Tolerance	$\pm 5\%$
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)30 mOhmOperating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.260" L x 0.512" W (32.00mm x 13.00mm)Height - Seated (Max)0.886" (22.50mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsHigh Pulse, DV/DTFeatures-	Voltage Rating - AC	220V
ESR (Equivalent Series Resistance)30 mOhmOperating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.260" L x 0.512" W (32.00mm x 13.00mm)Height - Seated (Max)0.886" (22.50mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsHigh Pulse, DV/DTFeatures-	Voltage Rating - DC	400V
Operating Temperature-55°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.260" L x 0.512" W (32.00mm x 13.00mm)Height - Seated (Max)0.886" (22.50mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsHigh Pulse, DV/DTFeatures-	Dielectric Material	Polypropylene (PP), Metallized
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension1.260" L x 0.512" W (32.00mm x 13.00mm)Height - Seated (Max)0.886" (22.50mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsHigh Pulse, DV/DTFeatures-	ESR (Equivalent Series Resistance)	30 mOhm
Package / CaseRadialSize / Dimension1.260" L x 0.512" W (32.00mm x 13.00mm)Height - Seated (Max)0.886" (22.50mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsHigh Pulse, DV/DTFeatures-	Operating Temperature	$-55^{\circ}C \sim 105^{\circ}C$
Size / Dimension 1.260" L x 0.512" W (32.00mm x 13.00mm) Height - Seated (Max) 0.886" (22.50mm) Termination PC Pins Lead Spacing 1.083" (27.50mm) Applications High Pulse, DV/DT Features -	Mounting Type	Through Hole
Height - Seated (Max)0.886" (22.50mm)TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsHigh Pulse, DV/DTFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing1.083" (27.50mm)ApplicationsHigh Pulse, DV/DTFeatures-	Size / Dimension	1.260" L x 0.512" W (32.00mm x 13.00mm)
Lead Spacing1.083" (27.50mm)ApplicationsHigh Pulse, DV/DTFeatures-	Height - Seated (Max)	0.886" (22.50mm)
Applications High Pulse, DV/DT Features -	Termination	PC Pins
Features -	Lead Spacing	1.083" (27.50mm)
	Applications	High Pulse, DV/DT
Papert arrors?	Features	-
Report errors:		Report errors?

171684J400Q-F Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

171684J400Q-F Payment Methods





If you have any question about 171684J400Q-F, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com