

172-015-212-911

172-015-212-911 Information

	Part Numbe
A	Manufactur
www.heisener.com	Category
Contraction of the	Description
1	Package

lumber	172-015-212-911
facturer	NorComp Inc.
ory	Connectors, Interconnects D-Sub Connectors
ption	CONN D-SUB RCPT 15P PNL MNT SLDR
ge	-
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



172-015-212-911 Specifications

Manufacturer NorComp Inc. Category Connectors, Interconnects D-Sub Connectors D-Sub Connectors Package - Series 172 Connector Style D-Sub Connectors Connector Type Receptacle, Female Sockets Number of Positions 15 Number of Rows 2 Shell Size, Connector Layout 2 (DA, A) Contact Type Signal Mounting Type Panel Mount, Through Hole Flange Feature Board Sciel (4-40); Mating Side, Female Screwlock (4-40) Flange Features Solder Features Board Lock Shell Material, Finish Steel, Tin Plated Contact Finish Thickness Filash		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-Series172Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions15Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureBoard Side (4-40); Mating Side, Female Screwlock (4-40)FeaturesSolderShell Material, FinishSteel, Tin PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Manufacturer Part Number	172-015-212-911
D-Sub ConnectorsPackage-Series172Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureBoard Side (4-40); Mating Side, Female Screwlock (4-40)FeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Manufacturer	NorComp Inc.
Package-Series172Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureBoard Side (4-40); Mating Side, Female Screwlock (4-40)Flange FeaturesSolderShell Material, FinishSeel, Tin PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Category	Connectors, Interconnects
Series172Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureBoard Side (4-40); Mating Side, Female Screwlock (4-40)FeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-SubConnector TypeReceptacle, Female SocketsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureBoard Side (4-40); Mating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Package	-
Connector TypeReceptacle, Female SocketsNumber of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureBoard Side (4-40); Mating Side, Female Screwlock (4-40)FeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Series	172
Number of Positions15Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureBoard Side (4-40); Mating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact Finish ThicknessFlashIngress Protection-UL94 V-0UL94 V-0	Connector Style	D-Sub
Number of Rows2Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureBoard Side (4-40); Mating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Connector Type	Receptacle, Female Sockets
Shell Size, Connector Layout2 (DA, A)Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureBoard Side (4-40); Mating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact Finish ThicknessGoldIngress Protection-Material Flammability RatingUL94 V-0	Number of Positions	15
Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeaturesBoard Side (4-40); Mating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Number of Rows	2
Mounting TypePanel Mount, Through HoleFlange FeatureBoard Side (4-40); Mating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	2 (DA, A)
Flange FeatureBoard Side (4-40); Mating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal
TerminationSolderFeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Panel Mount, Through Hole
FeaturesBoard LockShell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Board Side (4-40); Mating Side, Female Screwlock (4-40)
Shell Material, FinishSteel, Tin PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Termination	Solder
Contact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Features	Board Lock
Contact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel, Tin Plated
Ingress Protection-Material Flammability RatingUL94 V-0	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	Flash
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
		Report errors?

172-015-212-911 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE UARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

172-015-212-911 Payment Methods





If you have any question about 172-015-212-911, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com