

1763240000 Information

Heisener.com

Manufacturer Weidmuller

Category Connectors, Interconnects

1763240000

Terminal Blocks - Din Rail, Channel

Description CONN TERM BLK DISCONN 12-26AWG

Package -

Part Number

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









1763240000 Specifications

Manufacturer Part Number 1763240000 Manufacturer Weidmuller Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series Z Type Disconnect Disconnect Type Fuse, Removable Plug Number of Positions 4 Number of Levels 2 Terminal - Width 5.1mm Termination Style Push In, Spring Current - IEC 6.3A Voltage - IEC 400V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG 12-26 AWG Wire Gauge or Range - mm² 0.5-4mm² Features LED Color Beige		
Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series Z Type Disconnect Disconnect Type Fuse, Removable Plug Number of Positions 4 Number of Levels 2 Terminal - Width 5.1mm Termination Style Push In, Spring Current - IEC 6.3A Voltage - IEC 400V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG 12-26 AWG Wire Gauge or Range - mm² 0.5-4mm² Features LED	Manufacturer Part Number	1763240000
Package Series Z Type Disconnect Disconnect Type Fuse, Removable Plug Number of Positions 4 Number of Levels 2 Terminal - Width Termination Style Push In, Spring Current - IEC 6.3A Voltage - IEC 400V Current - UL Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Teminal Blocks - Din Rail, Channel - In Rail, Channel - In Rail, C	Manufacturer	Weidmuller
Package - Series Z Type Disconnect Disconnect Type Fuse, Removable Plug Number of Positions 4 Number of Levels 2 Terminal - Width 5.1mm Termination Style Push In, Spring Current - IEC 6.3A Voltage - IEC 400V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG 12-26 AWG Wire Gauge or Range - mm² 0.5-4mm² Features LED	Category	Connectors, Interconnects
Series Z Type Disconnect Disconnect Type Fuse, Removable Plug Number of Positions 4 Number of Levels 2 Terminal - Width 5.1mm Termination Style Push In, Spring Current - IEC 6.3A Voltage - IEC 400V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG 12-26 AWG Wire Gauge or Range - mm² 0.5-4mm² Features LED		Terminal Blocks - Din Rail, Channel
Type Disconnect Disconnect Type Fuse, Removable Plug Number of Positions 4 Number of Levels 2 Terminal - Width 5.1mm Termination Style Push In, Spring Current - IEC 6.3A Voltage - IEC 400V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG 12-26 AWG Wire Gauge or Range - mm² 0.5-4mm² Features LED	Package	-
Disconnect Type Fuse, Removable Plug Number of Positions 4 Number of Levels 2 Terminal - Width Termination Style Push In, Spring Current - IEC 6.3A Voltage - IEC 400V Current - UL 10A Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Features Fuse, Removable Plug Fuse, Removable Plug Fuse, Removable Plug A 40 40 40 5.1mm Push In, Spring 6.3A 400V 6.3A 400V 6.3A Voltage - IEC 400V 6.3A Voltage - UL 10A Voltage - UL	Series	Z
Number of Positions 4 Number of Levels 2 Terminal - Width 5.1mm Termination Style Push In, Spring Current - IEC 6.3A Voltage - IEC 400V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG 12-26 AWG Wire Gauge or Range - mm² 0.5-4mm² Features LED	Туре	Disconnect
Number of Levels2Terminal - Width5.1mmTermination StylePush In, SpringCurrent - IEC6.3AVoltage - IEC400VCurrent - UL10AVoltage - UL300VWire Gauge or Range - AWG12-26 AWGWire Gauge or Range - mm²0.5-4mm²FeaturesLED	Disconnect Type	Fuse, Removable Plug
Terminal - Width Termination Style Push In, Spring Current - IEC 6.3A Voltage - IEC 400V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features 5.1mm 5.1mm 10A 400V 6.3A 400V 10A 10A 10A 10A 10A 12-26 AWG LED	Number of Positions	4
Termination Style Current - IEC 6.3A Voltage - IEC 400V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Push In, Spring 6.3A 400V 400V 10A 10A 10A 10A 12-26 AWG LED	Number of Levels	2
Current - IEC 6.3A Voltage - IEC 400V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG 12-26 AWG Wire Gauge or Range - mm² 0.5-4mm² Features LED	Terminal - Width	5.1mm
Voltage - IEC 400V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG 12-26 AWG Wire Gauge or Range - mm² 0.5-4mm² Features LED	Termination Style	Push In, Spring
Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG 12-26 AWG Wire Gauge or Range - mm² 0.5-4mm² Features LED	Current - IEC	6.3A
Voltage - UL Wire Gauge or Range - AWG 12-26 AWG Wire Gauge or Range - mm² 0.5-4mm² Features LED	Voltage - IEC	400V
Wire Gauge or Range - AWG Wire Gauge or Range - mm ² Features 12-26 AWG 0.5-4mm ² LED	Current - UL	10A
Wire Gauge or Range - mm ² Features 0.5-4mm ² LED	Voltage - UL	300V
Features LED	Wire Gauge or Range - AWG	12-26 AWG
	Wire Gauge or Range - mm ²	0.5-4mm ²
Color Beige	Features	LED
	Color	Beige
Report errors?		Report errors?

1763240000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

1763240000 Payment Methods

































If you have any question about 1763240000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com