

1763260000 Information

Heisener.com

Part Number 1763260000 **Manufacturer** Weidmuller

Category Connectors, Interconnects

Terminal Blocks - Din Rail, Channel

Description CONN TERM BLK DISCONN 12-26AWG

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









1763260000 Specifications

Manufacturer Part Number 1763260000 Manufacturer Weidmuller Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series Z Type Disconnect Disconnect Type Fuse, Removable Plug Number of Positions 4 Number of Levels 2 Terminal - Width 5.1mm Termination Style Push In, Spring Current - IEC 6.3A Voltage - IEC 400V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG 12-26 AWG Wire Gauge or Range - mm² 0.5-4mm² Features LED Color Beige		
Category Connectors, Interconnects Terminal Blocks - Din Rail, Channel Package - Series Z Type Disconnect Disconnect Type Fuse, Removable Plug Number of Positions 4 Number of Levels 2 Terminal - Width 5.1mm Termination Style Push In, Spring Current - IEC 6.3A Voltage - IEC 400V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features Color Beige	Manufacturer Part Number	1763260000
Package - Series Z Type Disconnect Disconnect Type Fuse, Removable Plug Number of Positions 4 Number of Levels 2 Terminal - Width 5.1mm Termination Style Push In, Spring Current - IEC 6.3A Voltage - IEC 400V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG Wire Gauge or Range - mm² 0.5-4mm² Features Color Beige	Manufacturer	Weidmuller
Package - Series Z Type Disconnect Disconnect Type Fuse, Removable Plug Number of Positions 4 Number of Levels 2 Terminal - Width 5.1mm Termination Style Push In, Spring Current - IEC 6.3A Voltage - IEC 400V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG 12-26 AWG Wire Gauge or Range - mm² 0.5-4mm² Features LED Color Beige	Category	Connectors, Interconnects
Series Z Type Disconnect Disconnect Type Fuse, Removable Plug Number of Positions 4 Number of Levels 2 Terminal - Width 5.1mm Termination Style Push In, Spring Current - IEC 6.3A Voltage - IEC 400V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG 12-26 AWG Wire Gauge or Range - mm² 0.5-4mm² Features LED Color Beige		Terminal Blocks - Din Rail, Channel
Type Disconnect Disconnect Type Fuse, Removable Plug Number of Positions 4 Number of Levels 2 Terminal - Width 5.1mm Termination Style Push In, Spring Current - IEC 6.3A Voltage - IEC 400V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG 12-26 AWG Wire Gauge or Range - mm² 0.5-4mm² Features LED Color Beige	Package	-
Disconnect Type Number of Positions 4 Number of Levels 2 Terminal - Width 5.1mm Termination Style Push In, Spring Current - IEC 6.3A Voltage - IEC 400V Current - UL 10A Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - awG Wire Gauge or Range - mm² Features Color Fuse, Removable Plug Fuse, Removable Plug Fuse, Removable Plug A 40 A 40 Disconnect Type Push In, Spring 10.3A Push In, Spring 10.3A 10.4 10.4 10.5 10.	Series	Z
Number of Positions Number of Levels 2 Terminal - Width 5.1mm Termination Style Push In, Spring Current - IEC 6.3A Voltage - IEC 400V Current - UL 10A Voltage - UL Wire Gauge or Range - AWG Wire Gauge or Range - mm² Peatures LED Color 8eige	Туре	Disconnect
Number of Levels 2 Terminal - Width 5.1mm Termination Style Push In, Spring Current - IEC 6.3A Voltage - IEC 400V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG 12-26 AWG Wire Gauge or Range - mm² 0.5-4mm² Features LED Color Beige	Disconnect Type	Fuse, Removable Plug
Terminal - Width Termination Style Push In, Spring Current - IEC 6.3A Voltage - IEC 400V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features LED Color Sering Push In, Spring 1.240 6.3A 1.240	Number of Positions	4
Termination Style Current - IEC 6.3A Voltage - IEC 400V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG Wire Gauge or Range - mm² Features LED Color Push In, Spring 6.3A 400V 400V 400V 400V 400V 10A 400V 10A 400V 10A 10A 10A 10-26 AWG 12-26 AWG 12-26 AWG 12-26 AWG 12-26 AWG	Number of Levels	2
Current - IEC 6.3A Voltage - IEC 400V Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG 12-26 AWG Wire Gauge or Range - mm² 0.5-4mm² Features LED Color Beige	Terminal - Width	5.1mm
Voltage - IEC Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG Wire Gauge or Range - mm² 0.5-4mm² Features LED Color Beige	Termination Style	Push In, Spring
Current - UL 10A Voltage - UL 300V Wire Gauge or Range - AWG 12-26 AWG Wire Gauge or Range - mm² 0.5-4mm² Features LED Color Beige	Current - IEC	6.3A
Voltage - UL300VWire Gauge or Range - AWG12-26 AWGWire Gauge or Range - mm²0.5-4mm²FeaturesLEDColorBeige	Voltage - IEC	400V
Wire Gauge or Range - AWG Wire Gauge or Range - mm² 0.5-4mm² Features LED Color Beige	Current - UL	10A
Wire Gauge or Range - mm² Features Color Discretely a series of the s	Voltage - UL	300V
Features LED Color Beige	Wire Gauge or Range - AWG	12-26 AWG
Color Beige	Wire Gauge or Range - mm ²	0.5-4mm ²
	Features	LED
Report errors?	Color	Beige
Report ciros:		Report errors?

1763260000 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

1763260000 Payment Methods



















1763260000 Shipping Methods













If you have any question about 1763260000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com