

180-062-213R911

180-062-213R911 Information

Heisener.com	Part Number Manufacturer Category Description Package	180-062-213R911 NorComp Inc. Connectors, Interconnects D-Sub Connectors CONN D-SUB HD RCPT 62POS PNL MNT - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



180-062-213R911 Specifications

Manufacturer NorComp Inc. Connectors, Interconnects D-Sub Connectors Package - Series 180 Connector Style D-Sub, High Density Connector Type Receptacle, Female Sockets Number of Positions 62 Shell Size, Connector Layout 4 (DC, C) High Density Contact Type Signal Mounting Type Solder Flange Feature Board Side (4-40); Mating Side, Female Screwlock (4-40) Flange Features Solder Shell Material, Finish Stell, Nickel Plated Contact Finish Thickness Gold Contact Finish Thickness Flash Ingress Protection July 4-0		
CategoryConnectors, InterconnectsD-Sub ConnectorsPackage-Series180Connector StyleD-Sub, High DensityConnector TypeReceptacle, Female SocketsNumber of Positions62Shell Size, Connector Layout4 (DC, C) High DensityContact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureBoard Side (4-40); Mating Side, Female Screwlock (4-40)FeaturesBoard Lock, ShieldedShell Material, FinishSteel, Nickel PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-O	Manufacturer Part Number	180-062-213R911
D-Sub ConnectorsPackage-Series180Connector StyleD-Sub, High DensityConnector TypeReceptacle, Female SocketsNumber of Positions62Number of Rows3Shell Size, Connector Layout4 (DC, C) High DensityContact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureBoard Side (4-40); Mating Side, Female Screwlock (4-40)FeaturesBoard Lock, ShieldedShell Material, FinishSteel, Nickel PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Manufacturer	NorComp Inc.
Package-Series180Connector StyleD-Sub, High DensityConnector TypeReceptacle, Female SocketsNumber of Positions62Number of Rows3Shell Size, Connector Layout4 (DC, C) High DensityContact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureBoard Side (4-40); Mating Side, Female Screwlock (4-400)FeaturesBoard Lock, ShieldedShell Material, FinishSteel, Nickel PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Category	Connectors, Interconnects
Series180Connector StyleD-Sub, High DensityConnector TypeReceptacle, Female SocketsNumber of Positions62Number of Rows3Shell Size, Connector Layout4 (DC, C) High DensityContact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureBoard Side (4-40); Mating Side, Female Screwlock (4-40)FeaturesBoard Lock, ShieldedShell Material, FinishSteel, Nickel PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0		D-Sub Connectors
Connector StyleD-Sub, High DensityConnector TypeReceptacle, Female SocketsNumber of Positions62Number of Rows3Shell Size, Connector Layout4 (DC, C) High DensityContact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureBoard Side (4-40); Mating Side, Female Screwlock (4-40)FeaturesBoard Lock, ShieldedShell Material, FinishSteel, Nickel PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Package	-
Connector TypeReceptacle, Female SocketsNumber of Positions62Number of Rows3Shell Size, Connector Layout4 (DC, C) High DensityContact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureBoard Side (4-40); Mating Side, Female Screwlock (4-40)FeaturesBoard Lock, ShieldedShell Material, FinishSteel, Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Series	180
Number of Positions62Number of Rows3Shell Size, Connector Layout4 (DC, C) High DensityContact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureBoard Side (4-40); Mating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, ShieldedShell Material, FinishSteel, Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Connector Style	D-Sub, High Density
Number of Rows3Shell Size, Connector Layout4 (DC, C) High DensityContact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureBoard Side (4-40); Mating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, ShieldedShell Material, FinishSteel, Nickel PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Connector Type	Receptacle, Female Sockets
Shell Size, Connector Layout4 (DC, C) High DensityContact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureBoard Side (4-40); Mating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, ShieldedShell Material, FinishSteel, Nickel PlatedContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Number of Positions	62
Contact TypeSignalMounting TypePanel Mount, Through HoleFlange FeatureBoard Side (4-40); Mating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, ShieldedShell Material, FinishSteel, Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Number of Rows	3
Mounting TypePanel Mount, Through HoleFlange FeatureBoard Side (4-40); Mating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, ShieldedShell Material, FinishSteel, Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Shell Size, Connector Layout	4 (DC, C) High Density
Flange FeatureBoard Side (4-40); Mating Side, Female Screwlock (4-40)TerminationSolderFeaturesBoard Lock, ShieldedShell Material, FinishSteel, Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Contact Type	Signal
TerminationSolderFeaturesBoard Lock, ShieldedShell Material, FinishSteel, Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Mounting Type	Panel Mount, Through Hole
FeaturesBoard Lock, ShieldedShell Material, FinishSteel, Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Flange Feature	Board Side (4-40); Mating Side, Female Screwlock (4-40)
Shell Material, FinishSteel, Nickel PlatedContact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Termination	Solder
Contact FinishGoldContact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Features	Board Lock, Shielded
Contact Finish ThicknessFlashIngress Protection-Material Flammability RatingUL94 V-0	Shell Material, Finish	Steel, Nickel Plated
Ingress Protection-Material Flammability RatingUL94 V-0	Contact Finish	Gold
Material Flammability Rating UL94 V-0	Contact Finish Thickness	Flash
	Ingress Protection	-
Report errors?	Material Flammability Rating	UL94 V-0
		Report errors?

180-062-213R911 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

180-062-213R911 Payment Methods



180-062-213R911 Shipping Methods



If you have any question about 180-062-213R911, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com