

# 1805940000

### 1805940000 Information

Heisener.com	Part Number Manufacturer Category Description Package	1805940000 Weidmuller Connectors, Interconnects Terminal Blocks - Din Rail, Channel CONN TERM BLK FEED THRU 12-26AWG - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## 1805940000 Specifications

CategoryConnectors, Interconnects Terminal Blocks - Din Rail, ChannelPackage-Package-SeriesZTypeFeed Through (2), IsolatedDisconnect Type-Number of Positions5Number of Levels3; 1 GroundedTerminal - Width5.1mmTermination StylePush In, SpringCurrent - IEC24AVoltage - IEC800VVoltage - UL00VVoltage - MAG5.00VWire Gauge or Range - AWG12-26 AWGFeatures-Features-		
CategoryConnectors, InterconnectsTerminal Blocks - Din Rail, ChannelPackage-SeriesZTypeFeed Through (2), IsolatedDisconnect Type-Number of Positions5Number of Levels3; 1 GroundedTerminal - Width5.1mmTermination StylePush In, SpringCurrent - IEC24AVoltage - IEC800VCurrent - UL20AVoltage - MAG1.2-26 AWGWire Gauge or Range - AWG5-4mm²Features-<	Manufacturer Part Number	1805940000
Terminal Blocks - Din Rail, ChannelPackage-SeriesZTypeFeed Through (2), IsolatedDisconnect Type-Number of Positions5Number of Levels3; 1 GroundedTerminal - Width5.1mmTermination StylePush In, SpringCurrent - IEC24AVoltage - IEC800VCurrent - UL0AVoltage - UL600VWire Gauge or Range - AWG1.2-26 AWGWire Gauge or Range - mm²-ColorBeige	Manufacturer	Weidmuller
Package-SeriesZTypeFeed Through (2), IsolatedDisconnect Type-Number of Positions5Number of Levels3; 1 GroundedTerminal - Width5.1mmTermination StylePush In, SpringCurrent - IEC24AVoltage - IEC800VCurrent - UL00AVoltage or Range - AWG12-26 AWGWire Gauge or Range - AMG0.5-4mm²Features-ColorBeige	Category	Connectors, Interconnects
SeriesZTypeFeed Through (2), IsolatedDisconnect Type-Number of Positions5Number of Levels3; 1 GroundedTerminal - Width5.1mmTermination StylePush In, SpringCurrent - IEC24AVoltage - IEC800VCurrent - UL20AVoltage or Range - AWG12-26 AWGWire Gauge or Range - and Partice0.5-4mm²Features-ColorBeige		Terminal Blocks - Din Rail, Channel
TypeFeed Through (2), IsolatedDisconnect Type-Number of Positions5Number of Levels3; 1 GroundedTerminal - Width5.1mmTermination StylePush In, SpringCurrent - IEC24AVoltage - IEC800VCurrent - UL04Voltage or Range - AWG12-26 AWGWire Gauge or Range - mm²0.5-4mm²Features-ColorBeige	Package	-
Disconnect Type-Disconnect Type-Number of Positions5Number of Levels3; 1 GroundedTerminal - Width5.1mmTermination StylePush In, SpringCurrent - IEC24AVoltage - IEC800VCurrent - UL20AVoltage - UL600VWire Gauge or Range - AWG12-26 AWGWire Gauge or Range - mm²0.5-4mm²Features-ColorBeige	Series	Ζ
Number of Positions5Number of Levels3; 1 GroundedTerminal - Width5.1mmTermination StylePush In, SpringCurrent - IEC24AVoltage - IEC800VCurrent - UL20AVoltage - UL600VWire Gauge or Range - AWG12-26 AWGWire Gauge or Range - mm²0.5-4mm²Features-ColorBeige	Туре	Feed Through (2), Isolated
Number of Levels3; 1 GroundedTerminal - Width5.1mmTermination StylePush In, SpringCurrent - IEC24AVoltage - IEC800VCurrent - UL00AVoltage - UL600VWire Gauge or Range - AWG12-26 AWGWire Gauge or Range - mm²0.5-4mm²Features-ColorBeige	Disconnect Type	-
Terminal - Width5.1mmTermination StylePush In, SpringCurrent - IEC24AVoltage - IEC800VCurrent - UL20AVoltage - UL600VWire Gauge or Range - AWG12-26 AWGWire Gauge or Range - mm²0.5-4mm²Features-ColorBeige	Number of Positions	5
Termination StylePush In, SpringCurrent - IEC24AVoltage - IEC800VCurrent - UL20AVoltage - UL600VWire Gauge or Range - AWG12-26 AWGWire Gauge or Range - mm²0.5-4mm²Features-ColorBeige	Number of Levels	3; 1 Grounded
Current - IEC24AVoltage - IEC800VCurrent - UL20AVoltage - UL600VWire Gauge or Range - AWG12-26 AWGWire Gauge or Range - mm²0.5-4mm²Features-ColorBeige	Terminal - Width	5.1mm
Voltage - IEC800VCurrent - UL20AVoltage - UL600VWire Gauge or Range - AWG12-26 AWGWire Gauge or Range - mm²0.5-4mm²Features-ColorBeige	Termination Style	Push In, Spring
Current - UL20AVoltage - UL600VWire Gauge or Range - AWG12-26 AWGWire Gauge or Range - mm²0.5-4mm²Features-ColorBeige	Current - IEC	24A
Voltage - UL600VWire Gauge or Range - AWG12-26 AWGWire Gauge or Range - mm²0.5-4mm²Features-ColorBeige	Voltage - IEC	800V
Wire Gauge or Range - AWG12-26 AWGWire Gauge or Range - mm²0.5-4mm²Features-ColorBeige	Current - UL	20A
Wire Gauge or Range - mm²0.5-4mm²Features-ColorBeige	Voltage - UL	600V
Features - Color Beige	Wire Gauge or Range - AWG	12-26 AWG
Color Beige	Wire Gauge or Range - mm <sup>2</sup>	0.5-4mm <sup>2</sup>
	Features	-
Report errors?	Color	Beige
		Report errors?

#### 1805940000 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE ELARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# 1805940000 Payment Methods $\swarrow$ WIRE ransfer PayPai 2000 OneyGram Aiper 1000 100

If you have any question about 1805940000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com