



1808AC103KAZ1A Information



For Reference Only

Part Number 1808AC103KAZ1A Manufacturer AVX Corporation

Category Capacitors

Ceramic Capacitors

Description CAP CER 10000PF 1KV X7R 1808

Package 1808 (4520 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









1808AC103KAZ1A Specifications

Manufacturer Part Number 1808AC103KAZ1A Manufacturer AVX Corporation Category Capacitors Package 1808 (4520 Metric) Series FLEXITERM? Capacitance 10000pF Tolerance ±10% Voltage - Rated 1000V (1kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.180" L x 0.080" W (4.57mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.080" (2.03mm) Lead Spacing - Lead Style -		
Category Capacitors Package 1808 (4520 Metric) Series FLEXITERM? Capacitance 10000pF Tolerance ±10% Voltage - Rated 1000V (1kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.180" L x 0.080" W (4.57mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.080" (2.03mm) Lead Spacing - Lead Style -	Manufacturer Part Number	1808AC103KAZ1A
Package 1808 (4520 Metric) Series FLEXITERM? Capacitance 10000pF Tolerance ±10% Voltage - Rated 1000V (1kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.180" L x 0.080" W (4.57mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.080" (2.03mm) Lead Spacing - Lead Style -	Manufacturer	AVX Corporation
Package 1808 (4520 Metric) Series FLEXITERM? Capacitance 10000pF Tolerance ±10% Voltage - Rated 1000V (1kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.180" L x 0.080" W (4.57mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.080" (2.03mm) Lead Spacing - Lead Style -	Category	Capacitors
Series FLEXITERM? Capacitance 10000pF Tolerance ±10% Voltage - Rated 1000V (1kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.180" L x 0.080" W (4.57mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.080" (2.03mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 10000pF Tolerance ±10% Voltage - Rated 1000V (1kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.180" L x 0.080" W (4.57mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.080" (2.03mm) Lead Spacing - Lead Style -	Package	1808 (4520 Metric)
Tolerance ±10% Voltage - Rated 1000V (1kV) Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.180" L x 0.080" W (4.57mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.080" (2.03mm) Lead Spacing - Lead Style -	Series	FLEXITERM?
Voltage - Rated1000V (1kV)Temperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesSoft Termination, High VoltageRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.180" L x 0.080" W (4.57mm x 2.03mm)Height - Seated (Max)-Thickness (Max)0.080" (2.03mm)Lead Spacing-Lead Style-	Capacitance	10000pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style X7R A7R A7R A7R A7R -55°C ~ 125°C Soft Termination, High Voltage Soft Termination, High Voltage Soft Termination, High Voltage A1808 Voltage - Soft Termination, High Voltage Soft Termination, High Voltage A1808 Voltage - Soft Termination, High Voltage Boardflex Sensitive - Soft Termination, High Voltage Boardflex Sensitive - Soft Termination, High Voltage Soft Termination, High Voltage Soft Termination, High Voltage Boardflex Sensitive - Soft Termination, High Voltage - Soft Termination, High Voltage Boardflex Sensitive - Soft Termination, High Voltage - Soft Termination, High Voltage - Soft Termination, High Voltage Boardflex Sensitive - Soft Termination, High Voltage - Soft Termination, High Voltage Boardflex Sensitive - Soft Termination, High Voltage Boardflex Sensitive	Tolerance	±10%
Operating Temperature -55°C ~ 125°C Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension Height - Seated (Max) - Thickness (Max) 0.080" (2.03mm) Lead Spacing Lead Style - Soft Termination, High Voltage Soft Termination, High Voltage - Soft Termination -	Voltage - Rated	1000V (1kV)
Features Soft Termination, High Voltage Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.180" L x 0.080" W (4.57mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.080" (2.03mm) Lead Spacing - Lead Style -	Temperature Coefficient	X7R
Ratings - Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.180" L x 0.080" W (4.57mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.080" (2.03mm) Lead Spacing - Lead Style - Surface Mount, MLCC	Operating Temperature	-55°C ~ 125°C
Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.180" L x 0.080" W (4.57mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.080" (2.03mm) Lead Spacing - Lead Style -	Features	Soft Termination, High Voltage
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.180" L x 0.080" W (4.57mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.080" (2.03mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.180" L x 0.080" W (4.57mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.080" (2.03mm) Lead Spacing - Lead Style -	Applications	Boardflex Sensitive
Package / Case 1808 (4520 Metric) Size / Dimension 0.180" L x 0.080" W (4.57mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.080" (2.03mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.180" L x 0.080" W (4.57mm x 2.03mm) Height - Seated (Max) - Thickness (Max) 0.080" (2.03mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - -	Package / Case	1808 (4520 Metric)
Thickness (Max) 0.080" (2.03mm) Lead Spacing - Lead Style -	Size / Dimension	0.180" L x 0.080" W (4.57mm x 2.03mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.080" (2.03mm)
·	Lead Spacing	-
Report errors?	Lead Style	-
1		Report errors?

1808AC103KAZ1A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

1808AC103KAZ1A Payment Methods



















1808AC103KAZ1A Shipping Methods













If you have any question about 1808AC103KAZ1A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com