

1808J2K00271FCR

1808J2K00271FCR Information

Heisener.com	Part Number Manufacturer Category Description Package	1808J2K00271FCR Knowles Syfer Capacitors Ceramic Capacitors CAP CER 270PF 2KV C0G/NP0 1808 1808 (4520 Metric) For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



1808J2K00271FCR Specifications

AnanfacturerKnowles SyferCategoryCapacitorsCaranic CapacitorsCeranic CapacitorsPackage1808 (4520 Metric)Series-Capacitance270pFColerance±1%Voltage - Rated2000V (2kV)Cemperature CoefficientCOG, NP0 (1B)Operating Temperature55°C ~ 125°CSeatings-ApplicationsGeneral PurposeCalure Rate-ApplicationsSurface Mount AbleCalure Rate-Calure Rate-Seatings-Seatings-Calure Rate-Calure Rate-Calure Rate-Seatings-<		
Capacitors Ceramic Capacitors Package 1808 (4520 Metric) Package - Capacitance - Colerance 270pF Polerance ±1% Yoltage - Rated 2000V (2kV) Perperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Pertures Epoxy Mountable Pachage - Values Rated - Values Rates - Values Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Packages Coefficient - Values Rates - Values Rates - Values Rate - Values Rate - Values Rate - Values Rate - Values Case 1808 (4520 Metric) Values Joues 1808 (4520 Metric)	Manufacturer Part Number	1808J2K00271FCR
Ceramic CapacitorsPackage1808 (4520 Metric)Backage-Capacitance270pFColerance±1%Voltage - Rated2000V (2kV)Comperature CoefficientCOG, NP0 (1B)Operating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsGeneral PurposeFailure Rate-Aounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Bize / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)	Manufacturer	Knowles Syfer
Package1808 (4520 Metric)Beries-Capacitance270pFTolerance±1%Yoltage - Rated2000V (2kV)Cemperature CoefficientCOG, NP0 (1B)Operating Temperature-55°C ~ 125°CSeaturesEpoxy MountableRatings-ApplicationsGeneral PurposeSailure Rate-ApplicationsSurface Mount, MLCCPackage / Case1808 (4520 Metric)Bize / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)	Category	Capacitors
Genes-Capacitance270pFColerance±1%Voltage - Rated2000V (2kV)Comperature CoefficientCOG, NP0 (1B)Operating Temperature-55°C ~ 125°CSeaturesEpoxy MountableRatings-ApplicationsGeneral PurposeGalure Rate-Aounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.17" L x 0.079" W (4.50mm x 2.00mm)		Ceramic Capacitors
Capacitance270pFColerance±1%Yoltage - Rated2000V (2kV)Yomperature CoefficientCOG, NP0 (1B)Operating Temperature-55°C ~ 125°CSeaturesEpoxy MountableRatings-ApplicationsGeneral PurposeYouting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)	Package	1808 (4520 Metric)
Folerance±1%Yoltage - Rated2000V (2kV)Cemperature CoefficientCOG, NP0 (1B)Operating Temperature-55°C ~ 125°CSeaturesEpoxy MountableRatings-ApplicationsGeneral PurposeGailure Rate-Aounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)	Series	-
Zolow (2kV)Zemperature CoefficientC0G, NP0 (1B)Operating Temperature-55°C ~ 125°CZeaturesEpoxy MountableRatings-ApplicationsGeneral PurposeValure Rate-Aounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)	Capacitance	270pF
Comperature CoefficientCOG, NP0 (1B)Operating Temperature-55°C ~ 125°CSeaturesEpoxy MountableRatings-ApplicationsGeneral PurposeFailure Rate-Aounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)	Tolerance	±1%
Deperating Temperature-55°C ~ 125°CSeaturesEpoxy MountableRatings-ApplicationsGeneral PurposeSailure Rate-Aounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)	Voltage - Rated	2000V (2kV)
FractionEpoxy MountableBeaturesEpoxy MountableRatings-ApplicationsGeneral PurposeFailure Rate-Aounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Bize / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)	Temperature Coefficient	C0G, NP0 (1B)
Ratings-ApplicationsGeneral PurposeFailure Rate-Aounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)	Operating Temperature	-55°C ~ 125°C
ApplicationsGeneral PurposeFailure Rate-Aounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Bize / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)	Features	Epoxy Mountable
Failure Rate-Aounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)	Ratings	-
Aounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Bize / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)	Applications	General Purpose
Package / Case 1808 (4520 Metric) Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm)	Failure Rate	-
Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm)	Mounting Type	Surface Mount, MLCC
	Package / Case	1808 (4520 Metric)
Height - Seated (Max) -	Size / Dimension	0.177" L x 0.079" W (4.50mm x 2.00mm)
	Height - Seated (Max)	-
Chickness (Max) 0.079" (2.00mm)	Thickness (Max)	0.079" (2.00mm)
Lead Spacing -	Lead Spacing	-
	Lead Style	-
Report errors?		Report errors?

1808J2K00271FCR Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

1808J2K00271FCR Payment Methods





If you have any question about 1808J2K00271FCR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com