



1808J6300152JCT Information

Heisener.com

Part Number1808J6300152JCTManufacturerKnowles SyferCategoryCapacitors

Ceramic Capacitors

Description CAP CER 1500PF 630V C0G/NP0 1808

Package 1808 (4520 Metric)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









1808J6300152JCT Specifications

Manufacturer Part Number 1808J6300152JCT Manufacturer Knowles Syfer Category Capacitors Package 1808 (4520 Metric) Series - Capacitance 1500pF Tolerance ±5% Voltage - Rated 630V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -		
Category Capacitors Package 1808 (4520 Metric) Series - Capacitance 1500pF Tolerance ±5% Voltage - Rated 630V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Manufacturer Part Number	1808J6300152JCT
Package 1808 (4520 Metric) Series - Capacitance 1500pF Tolerance ±5% Voltage - Rated 630V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Manufacturer	Knowles Syfer
Package 1808 (4520 Metric) Series - Capacitance 1500pF Tolerance ±5% Voltage - Rated 630V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Category	Capacitors
Series - Capacitance 1500pF Tolerance ±5% Voltage - Rated 630V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 1500pF Tolerance ±5% Voltage - Rated 630V Temperature Coefficient COG, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Package	1808 (4520 Metric)
Tolerance ±5% Voltage - Rated 630V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Series	-
Voltage - Rated 630V Temperature Coefficient C0G, NP0 (1B) Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style	Capacitance	1500pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style	Tolerance	±5%
Operating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-Lead Style-	Voltage - Rated	630V
Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Temperature Coefficient	C0G, NP0 (1B)
Ratings - General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Features	Epoxy Mountable
Failure Rate Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Applications	General Purpose
Package / Case 1808 (4520 Metric) Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - -	Package / Case	1808 (4520 Metric)
Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Size / Dimension	0.177" L x 0.079" W (4.50mm x 2.00mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.079" (2.00mm)
·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

1808J6300152JCT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

1808J6300152JCT Payment Methods



















1808J6300152JCT Shipping Methods













If you have any question about 1808J6300152JCT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com