



1808Y0160564KXR Information

Heisener.com

Part Number 1808Y0160564KXR Manufacturer Knowles Syfer

Category Capacitors
Ceramic Capacitors

Description CAP CER 0.56UF 16V X7R 1808

Package 1808 (4520 Metric)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









1808Y0160564KXR Specifications

Manufacturer Part Number 1808Y0160564KXR Manufacturer Knowles Syfer Category Capacitors Package 1808 (4520 Metric) Series FlexiCap? Capacitance 0.56µF Tolerance ±10% Voltage - Rated 16V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -		
Category Capacitors Package 1808 (4520 Metric) Series FlexiCap? Capacitance 0.56μF Tolerance ±10% Voltage - Rated 16V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Manufacturer Part Number	1808Y0160564KXR
Package 1808 (4520 Metric) Series FlexiCap? Capacitance 0.56µF Tolerance ±10% Voltage - Rated 16V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Manufacturer	Knowles Syfer
Package 1808 (4520 Metric) Series FlexiCap? Capacitance 0.56μF Tolerance ±10% Voltage - Rated 16V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Category	Capacitors
Series FlexiCap? Capacitance 0.56µF Tolerance ±10% Voltage - Rated 16V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 0.56μF Tolerance ±10% Voltage - Rated 16V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Package	1808 (4520 Metric)
Tolerance ±10% Voltage - Rated 16V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Series	FlexiCap?
Voltage - Rated16VTemperature CoefficientX7R (2R1)Operating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-Lead Style-	Capacitance	0.56μF
Temperature Coefficient ATR (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style XTR (2R1) ATR (2R) A	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-Lead Style-	Voltage - Rated	16V
Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Temperature Coefficient	X7R (2R1)
Ratings - Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style	Operating Temperature	-55°C ~ 125°C
Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Features	Soft Termination
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Applications	Boardflex Sensitive
Package / Case 1808 (4520 Metric) Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - -	Package / Case	1808 (4520 Metric)
Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Size / Dimension	0.177" L x 0.079" W (4.50mm x 2.00mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.079" (2.00mm)
·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

1808Y0160564KXR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

1808Y0160564KXR Payment Methods



















1808Y0160564KXR Shipping Methods













If you have any question about 1808Y0160564KXR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com