

1808Y0250273GFR

1808Y0250273GFR Information

Heisener.com	Part Number Manufacturer Category Description Package	1808Y0250273GFR Knowles Syfer Capacitors Ceramic Capacitors CAP CER 0.027UF 25V C0G/NP0 1808 1808 (4520 Metric) For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



1808Y0250273GFR Specifications

IanufacturerKnowles SyferategoryCapacitorsackageCeramic Capacitorsackage1808 (4520 Metric)eriesRexiCap?apacitance0.027µFolerance±2%oltage - Rated25Vemperature CoefficientCOG, NPOperating Temperature-55°C ~ 125°Catings-aplicationsHigh TemperatureaplicationsSufface Mount, MLCCanduring Type1808 (4520 Metric)ackage / Case1808 (4520 Metric)ize / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)		
Ategory Capacitors ackage 1808 (4520 Metric) ackage 1808 (4520 Metric) eries FlexiCap? apacitance 0.027 μF olerance ±2% oltage - Rated 25V emperature Coefficient COG, NPO opperating Temperature -55°C ~ 125°C eatures High Temperature atings - applications High Reliability atingr Sype Surface Mount, MLCC ackage / Case 1808 (4520 Metric) ize / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm)	Manufacturer Part Number	1808Y0250273GFR
Ceramic Capacitorsackage1808 (4520 Metric)eriesFlexiCap?apacitance0.027μFolerance±2%oltage - Rated25Vemperature CoefficientC0G, NP0perating Temperature-55°C ~ 125°CeaturesHigh Temperatureatings-pilcationsHigh Reliabilityailure Rate-Surface Mount, MLCCSurface Mount, MLCCackage / Case1808 (4520 Metric)ize / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)	Manufacturer	Knowles Syfer
ackage1808 (4520 Metric)eriesFlexiCap?apacitance0.027µFolerance±2%oltage - Rated25Vroltage - RatedC0G, NPOperating Temperature-55°C ~ 125°CeaturesHigh Temperatureatings-pilcationsHigh Reliabilityailure Rate-Iounting TypeSurface Mount, MLCCackage / Case1808 (4520 Metric)ize / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)	Category	Capacitors
Previous FlexiCap? apacitance 0.027µF olerance ±2% oltage - Rated 25V oltage - Rated COG, NPO operating Temperature -55°C ~ 125°C eatures High Temperature atings - applications High Reliability atinge Type Surface Mount, MLCC founting Type 1808 (4520 Metric) ackage / Case 0.177" L x 0.079" W (4.50mm x 2.00mm)		Ceramic Capacitors
apacitance 0.027μF olerance ±2% oltage - Rated 25V emperature Coefficient C0G, NP0 perating Temperature -55°C ~ 125°C eatures High Temperature atings - pplications High Reliability ailure Rate - Iounting Type Surface Mount, MLCC ackage / Case 1808 (4520 Metric) oltare / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm)	Package	1808 (4520 Metric)
olerance±2%oltage - Rated25Vemperature CoefficientC0G, NP0operating Temperature-55°C ~ 125°CeaturesHigh Temperatureatings-pplicationsHigh Reliabilityailure Rate-founting TypeSurface Mount, MLCCackage / Case1808 (4520 Metric)aiter Jimension0.177" L x 0.079" W (4.50mm x 2.00mm)	Series	FlexiCap?
oltage - Rated25Vemperature CoefficientCOG, NPOperating Temperature-55°C ~ 125°CeaturesHigh Temperatureatings-pplications-atiure Rate-Iounting TypeSurface Mount, MLCCackage / Case1808 (4520 Metric)ize / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)	Capacitance	0.027µF
emperature CoefficientCOG, NPOperating Temperature-55°C ~ 125°CeaturesHigh Temperatureatings-applicationsHigh Reliabilityailure Rate-founting TypeSurface Mount, MLCCackage / Case1808 (4520 Metric)ize / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)	Tolerance	±2%
perating Temperature-55°C ~ 125°CeaturesHigh Temperatureatings-pplicationsHigh Reliabilityailure Rate-founting TypeSurface Mount, MLCCackage / Case1808 (4520 Metric)ize / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)	Voltage - Rated	25V
eatures High Temperature atings - applications High Reliability ailure Rate - founting Type Surface Mount, MLCC ackage / Case 1808 (4520 Metric) ize / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm)	Temperature Coefficient	COG, NPO
atings-pplicationsHigh Reliabilityailure Rate-Iounting TypeSurface Mount, MLCCackage / Case1808 (4520 Metric)ize / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)	Operating Temperature	-55°C ~ 125°C
pplicationsHigh Reliabilityailure Rate-founting TypeSurface Mount, MLCCackage / Case1808 (4520 Metric)ize / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)	Features	High Temperature
ailure Rate-Iounting TypeSurface Mount, MLCCackage / Case1808 (4520 Metric)ize / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)	Ratings	-
Iounting TypeSurface Mount, MLCCackage / Case1808 (4520 Metric)ize / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)	Applications	High Reliability
ackage / Case 1808 (4520 Metric) ize / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm)	Failure Rate	-
ize / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm)	Mounting Type	Surface Mount, MLCC
	Package / Case	1808 (4520 Metric)
aight Souted (Max)	Size / Dimension	0.177" L x 0.079" W (4.50mm x 2.00mm)
-	Height - Seated (Max)	-
hickness (Max) 0.079" (2.00mm)	Thickness (Max)	0.079" (2.00mm)
ead Spacing -	Lead Spacing	-
ead Style -	Lead Style	-
Report error		Report errors?

1808Y0250273GFR Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

1808Y0250273GFR Payment Methods



If you have any question about 1808Y0250273GFR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com