

1808Y0256P80CFT

1808Y0256P80CFT Information

Container com	Part Number Manufacturer Category Description Package	1808Y0256P80CFT Knowles Syfer Capacitors Ceramic Capacitors CAP CER 6.8PF 25V C0G/NP0 1808 1808 (4520 Metric) For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



1808Y0256P80CFT Specifications

Manufacturer Part Number I808Y0256P80CFT Manufacturer Knowles Syfer Category Capacitors Caranic Capacitors Ceranic Capacitors Package 1808 (4520 Metric) Series FexiCapacitors Capacitance 6.8pF Tolerance ±0.2pF Voltage - Rated 25V Porter Coefficient CoG, NPO Operating Temperature 55°C ~ 125°C Pactures High Temperature Applications High Reliability Applications Surface Mount, MLCC Package / Case 1808 (4520 Metric) Nourting Type Surface Mount, Surface Mount, Surface Size / Dimension 0.77" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Lead Spacing - Lead Spacing - Lead Spacing -	-	
CategoryCapacitorsPackage1808 (4520 Metric)SeriesFlexiCap?Capacitance6.8pFTolerance±0.25pFVoltage - Rated25VTemperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureApplications-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Hight - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-Lead Style-	Manufacturer Part Number	1808Y0256P80CFT
Caranic CapacitorsPackage1808 (4520 Metric)SeriesFlexiCap?Capacitance6.8pFTolerance±0.25pFVoltage - RatedCOG, NPOOperating TemperatureCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureApplications-Applicationsour fug PaceFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Lead Spacing-Lead Style-Lead Style-	Manufacturer	Knowles Syfer
Package1808 (4520 Metric)SeriesFlexiCap?Capacitance6.8pFTolerance40.25pFVoltage - Rated50°Operating Temperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureApplications-Applications TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Height - Seated (Max)0.079" (2.00mm)Lead Spacing-Lead Style-Starten-Lead Style-Starten-	Category	Capacitors
SeriesFlexiCap?Capacitance6.8pFTolerance±0.25pFVoltage - Rated25VTemperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCSize / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Hight - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-Lead Style-Starley <td></td> <td>Ceramic Capacitors</td>		Ceramic Capacitors
Capacitance6.8pTolerance±0.25pFVoltage - Rated25VTemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCSize / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Hight - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-Lead Style-	Package	1808 (4520 Metric)
Tolerance±0.25pFVoltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Lead Spacing0.079" (2.00mm)Lead Spacing-Lead Style-	Series	FlexiCap?
Voltage - Rated25VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1.017" L x 0.079" W (4.50mm x 2.00mm)Size / Dimension-Height - Seated (Max)-Lead Spacing-Lead Spacing-Lead Style-State Style	Capacitance	6.8pF
Temperature CoefficientCOG, NPOOperating Temperature-5°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Lead Spacing0.079" (2.00mm)Lead Style-State Style-	Tolerance	±0.25pF
Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-Lead Style-	Voltage - Rated	25V
FeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-Lead Style-	Temperature Coefficient	C0G, NP0
Ratings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-Lead Style-	Operating Temperature	-55°C ~ 125°C
ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-Lead Style-	Features	High Temperature
Failure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-Lead Style-	Ratings	-
Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-Lead Style-	Applications	High Reliability
Package / Case 1808 (4520 Metric) Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-Lead Style-	Package / Case	1808 (4520 Metric)
Thickness (Max)0.079" (2.00mm)Lead Spacing-Lead Style-	Size / Dimension	0.177" L x 0.079" W (4.50mm x 2.00mm)
Lead Spacing-Lead Style-	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.079" (2.00mm)
·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

1808Y0256P80CFT Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

1808Y0256P80CFT Payment Methods



If you have any question about 1808Y0256P80CFT, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com