

1808Y1000681GFT

1808Y1000681GFT Information

Container.com	Part Number Manufacturer Category Description Package	1808Y1000681GFT Knowles Syfer Capacitors Ceramic Capacitors CAP CER 680PF 100V C0G/NP0 1808 1808 (4520 Metric) For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



1808Y1000681GFT Specifications

Manufacturer Part Number IS08Y1000681GPT Manufacturer Knowles Syfer Category Capacitors Package I808 (4520 Metric) Package I808 (4520 Metric) Series FexiCap? Capacitance Stop F Tolerance ±2% Voltage - Rated 100V Series Cog, NPO Operating Temperature OSC ~ 125°C Pactage High Temperature Applications High Reliability Ratings - Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.717" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Thickness (Max) 0.707" (2.00mm)		
CategoryCapacitorsPackage1808 (4520 Metric)SeriesFlexiCap?Capacitance680pFTolerance±2%Voltage - Rated100VTemperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureApplications-ApplicationsSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Hight - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-Lead Style-	Manufacturer Part Number	1808Y1000681GFT
Ceramic CapacitorsPackage1808 (4520 Metric)SeriesFlexiCap?Capacitance680pFTolerance±2%Voltage - Rated100VTemperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureApplications-Applications-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Hight - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Style-Lead Style-	Manufacturer	Knowles Syfer
Package1808 (4520 Metric)SeriesFlexiCap?Capacitance680pFTolerance±2%Voltage - Rated100VTemperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureApplications-ApplicationsSurface Mount, MLCCNoutting TypeSol (4520 Metric)Size / Dimension.1017" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max).007" (2.00mm)Heidspacing.0179" (2.00mm)Lead Spacing.Lead Style.	Category	Capacitors
SeriesFlexiCap?Capacitance680pFTolerance±2%Voltage - Rated100VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCSize / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)High T- Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-Lead Style-Starten Starten-Starten Starten-Starten Starten-Starten Starten Starten-Starten Starten St		Ceramic Capacitors
Capacitance 680p. Tolerance ±2% Voltage - Rated 100V Temperature Coefficient COG, NPO Operating Temperature 55°C ~ 125°C Features High Temperature Attings - Applications High Reliability Failure Rate - Mounting Type Surface Mount, MLCC Stare / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Hight - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Package	1808 (4520 Metric)
Tolerance±2%Voltage - Rated100VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Lead Spaing0.079" (2.00mm)Lead Style-State Style-	Series	FlexiCap?
Voltage - RatedIOVTemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Lead Spacing-Lead Style-Lead Style-	Capacitance	680pF
Temperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Hight - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-Lead Style-	Tolerance	±2%
Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-Lead Style-	Voltage - Rated	100V
FeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-Lead Style-	Temperature Coefficient	C0G, NP0
Ratings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-Lead Style-	Operating Temperature	-55°C ~ 125°C
ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-Lead Style-	Features	High Temperature
Failure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-Lead Style-	Ratings	-
Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-Lead Style-	Applications	High Reliability
Package / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-Lead Style-	Failure Rate	-
Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-Lead Style-	Package / Case	1808 (4520 Metric)
Thickness (Max) 0.079" (2.00mm) Lead Spacing - Lead Style -	Size / Dimension	0.177" L x 0.079" W (4.50mm x 2.00mm)
Lead Spacing-Lead Style-	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.079" (2.00mm)
-	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

1808Y1000681GFT Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

1808Y1000681GFT Payment Methods



If you have any question about 1808Y1000681GFT, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com