

1808Y2000222FCR

1808Y2000222FCR Information

Heisener.com	Part Number Manufacturer Category Description Package	1808Y2000222FCR Knowles Syfer Capacitors Ceramic Capacitors CAP CER 2200PF 200V C0G/NP0 1808 1808 (4520 Metric) For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



1808Y2000222FCR Specifications

ManufacturerKnowles SyferCapacitorsCapacitorsCaranic CapacitorsPackage1808 (4520 Metric)SeriesFlexiCap?Capacitance200pFColerance±1%Voltage - Rated00VPremerature CoefficientCoG, NP0 (1B)Operating TemperatureSoft TerminationPackageSoft TerminationRatings-ApplicationsBoardflex SensitivePalitare Rate-ApplicationsSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)0.079" (2.00mm)		
CapacitorsCapacitorsPackage1808 (4520 Metric)PackageFlexiCap?Capacitance2200pFColerance±1%Voltage - Rated200VPremperature CoefficientCOG, NP0 (1B)Operating Temperature-55°C ~ 125°CPackageSoft TerminationRatings-ApplicationsBoardflex SensitivePackage / CaseSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)0.079" (2.00mm)	Manufacturer Part Number	1808Y2000222FCR
Ceramic CapacitorsPackage1808 (4520 Metric)PackageFlexiCap?Capacitance2200pFFolerance±1%Voltage - Rated200VPorenting Temperature CoefficientCOG, NP0 (1B)Derating Temperature>55°C ~ 125°CPactargeSoft TerminationRatings-ApplicationsBoardflex SensitivePackage / CaseSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.17" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)0.079" (2.00mm)	Manufacturer	Knowles Syfer
Package1808 (4520 Metric)BericsFlexiCap?Capacitance2200pFFolerance±1%Voltage - Rated200VComperature CoefficientCOG, NPO (1B)Dereating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Package / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)0.079" (2.00mm)	Category	Capacitors
SeriesFlexiCap?Capacitance2200pFColerance±1%Voltage - Rated200VComperature CoefficientCOG, NP0 (1B)Operating Temperature-55°C ~ 125°CSeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveSailure Rate-Voluning TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Chickness (Max)0.079" (2.00mm)		Ceramic Capacitors
Capacitance2200pFColerance±1%Voltage - Rated200VComperature CoefficientCOG, NP0 (1B)Operating Temperature-55°C ~ 125°CSoft TerminationSoft TerminationRatings-ApplicationsBoardflex SensitiveSailure Rate-Volunting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)0.079" (2.00mm)	Package	1808 (4520 Metric)
Folerance±1%Folerance200VComperature CoefficientCOG, NP0 (1B)Operating Temperature-55°C ~ 125°CSeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Avonting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)0.079" (2.00mm)	Series	FlexiCap?
Voltage - Rated200VFemperature CoefficientC0G, NP0 (1B)Operating Temperature-55°C ~ 125°CSeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Avonting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Chickness (Max)0.079" (2.00mm)	Capacitance	2200pF
Femperature CoefficientCOG, NP0 (1B)Operating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)0.079" (2.00mm)	Tolerance	±1%
Deperating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Fhickness (Max)0.079" (2.00mm)	Voltage - Rated	200V
FeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Aounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Bize / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Fhickness (Max)0.079" (2.00mm)	Temperature Coefficient	C0G, NP0 (1B)
Ratings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Fhickness (Max)0.079" (2.00mm)	Operating Temperature	-55°C ~ 125°C
ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Bize / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Fhickness (Max)0.079" (2.00mm)	Features	Soft Termination
FriFriFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Fhickness (Max)0.079" (2.00mm)	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1808 (4520 Metric) Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Fhickness (Max) 0.079" (2.00mm)	Applications	Boardflex Sensitive
Package / Case 1808 (4520 Metric) Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm)	Failure Rate	-
Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm)	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)-Chickness (Max)0.079" (2.00mm)	Package / Case	1808 (4520 Metric)
Chickness (Max) 0.079" (2.00mm)	Size / Dimension	0.177" L x 0.079" W (4.50mm x 2.00mm)
	Height - Seated (Max)	-
	Thickness (Max)	0.079" (2.00mm)
Lead Spacing -	Lead Spacing	-
Lead Style -	Lead Style	-
Report errors?		Report errors?

1808Y2000222FCR Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

1808Y2000222FCR Payment Methods



If you have any question about 1808Y2000222FCR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com