

1808Y2500390FCT

est a Quote

1808Y2500390FCT Information

Heisener.com	Part Number	1808Y2500390FCT	
	Manufacturer	Knowles Syfer	
	Category	Capacitors Ceramic Capacitors	
	Description	CAP CER 39PF 250V COG/NP0 1808	- 39
	Package	1808 (4520 Metric)	20
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Req

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



1808Y2500390FCT Specifications

ManufacturerKnowles SyferCapacitorsCapacitorsPackage1808 (4520 Metric)SeriesFlexiCap?Capacitance39pFColerance±1%Voltage - Rated250VTomperature CoefficientCOG, NP0 (1B)Operating TemperatureSoft TerminationPackageSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-ApplicationsSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Hickness (Max)0.079" (2.00mm)Lead Spacing-		
CategoryCapacitorsPackage1808 (4520 Metric)Package1808 (4520 Metric)SeriesFlexiCap?Capacitance39pFColerance±1%Voltage - Rated250VPoperature CoefficientCOG, NP0 (1B)Operating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-	Manufacturer Part Number	1808Y2500390FCT
Indext CapacitorsPackage1808 (4520 Metric)SeriesFlexiCap?Capacitance39pFTolerance±1%Voltage - Rated250VPemperature CoefficientCOG, NP0 (1B)Operating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Hickness (Max)0.079" (2.00mm)Lead Spacing-	Manufacturer	Knowles Syfer
Package1808 (4520 Metric)SeriesFlexiCap?Capacitance39pFTolerance±1%Voltage - Rated250VTomperature CoefficientCOG, NP0 (1B)Operating Temperature>55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Hickness (Max)0.079" (2.00mm)Lead Spacing-	Category	Capacitors
SeriesFlexiCap?Capacitance39pFTolerance±1%Voltage - Rated250VComperature CoefficientCOG, NPO (1B)Operating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension-Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-		Ceramic Capacitors
Capacitance39pFTolerance±1%Voltage - Rated250VTemperature CoefficientC0G, NP0 (1B)Operating Temperature-55°C ~ 125°CFeaturessSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Lead Spacing-	Package	1808 (4520 Metric)
Tolerance±1%Voltage - Rated250VTemperature CoefficientC0G, NP0 (1B)Operating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Lead Spacing-	Series	FlexiCap?
Voltage - Rated250VTemperature CoefficientCOG, NP0 (1B)Operating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Lead Spacing0.079" (2.00mm)	Capacitance	39pF
Temperature CoefficientCOG, NP0 (1B)Operating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-	Tolerance	±1%
Operating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-	Voltage - Rated	250V
FeaturesSoft TerminationFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-	Temperature Coefficient	C0G, NP0 (1B)
Ratings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-	Operating Temperature	-55°C ~ 125°C
ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-	Features	Soft Termination
Failure Rate-Failure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-	Ratings	-
Mounting TypeSurface Mount, MLCCPackage / Case1808 (4520 Metric)Size / Dimension0.177" L x 0.079" W (4.50mm x 2.00mm)Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-	Applications	Boardflex Sensitive
Package / Case 1808 (4520 Metric) Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing -	Failure Rate	-
Size / Dimension 0.177" L x 0.079" W (4.50mm x 2.00mm) Height - Seated (Max) - Thickness (Max) 0.079" (2.00mm) Lead Spacing -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)-Thickness (Max)0.079" (2.00mm)Lead Spacing-	Package / Case	1808 (4520 Metric)
Thickness (Max) 0.079" (2.00mm) Lead Spacing -	Size / Dimension	0.177" L x 0.079" W (4.50mm x 2.00mm)
Lead Spacing -	Height - Seated (Max)	-
	Thickness (Max)	0.079" (2.00mm)
Lead Style -	Lead Spacing	-
	Lead Style	-
Report errors?		Report errors?

1808Y2500390FCT Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

1808Y2500390FCT Payment Methods



If you have any question about 1808Y2500390FCT, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com