

180FM Information



For Reference Only

Part Number 180FM Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 180A 690VAC/500VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









180FM Specifications

Manufacturer Part Number 180FM Manufacturer Eaton Category Circuit Protection Package Cylindrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series FM Fuse Type Cartridge Current Rating 180A Voltage Rating - AC 690V Voltage Rating - DC 500V Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.969" L (38.10mm x 50.00mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesFMFuse TypeCartridgeCurrent Rating180AVoltage Rating - AC690VVoltage Rating - DC500VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.500" Dia x 1.969" L (38.10mm x 50.00mm)	Manufacturer Part Number	180FM
PackageElectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesFMFuse TypeCartridgeCurrent Rating180AVoltage Rating - AC690VVoltage Rating - DC500VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.500" Dia x 1.969" L (38.10mm x 50.00mm)	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)SeriesFMFuse TypeCartridgeCurrent Rating180AVoltage Rating - AC690VVoltage Rating - DC500VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.500" Dia x 1.969" L (38.10mm x 50.00mm)	Category	Circuit Protection
SeriesFMFuse TypeCartridgeCurrent Rating180AVoltage Rating - AC690VVoltage Rating - DC500VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.500" Dia x 1.969" L (38.10mm x 50.00mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating180AVoltage Rating - AC690VVoltage Rating - DC500VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-ApprovalsCE, UROperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.500" Dia x 1.969" L (38.10mm x 50.00mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 690V Voltage Rating - DC 500V Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 180A 690V 690V 690V 690V 690V 690V 690V 690V	Series	FM
Voltage Rating - AC Voltage Rating - DC Soov Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 690V 690V 690V 6000 CUN 6000 600	Fuse Type	Cartridge
Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals CE, UR Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 500V 500V 500V 500V 500V 500V 500V 6000	Current Rating	180A
Response Time	Voltage Rating - AC	690V
Applications Electrical, Industrial Features - Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.969" L (38.10mm x 50.00mm)	Voltage Rating - DC	500V
Features - Class - Class - CE, UR Approvals CE, UR Operating Temperature - Streaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.969" L (38.10mm x 50.00mm)	Response Time	-
Class - Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.969" L (38.10mm x 50.00mm)	Applications	Electrical, Industrial
Approvals CE, UR Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.969" L (38.10mm x 50.00mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.969" L (38.10mm x 50.00mm)	Class	-
Breaking Capacity @ Rated Voltage 200kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.969" L (38.10mm x 50.00mm)	Approvals	CE, UR
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.969" L (38.10mm x 50.00mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.500" Dia x 1.969" L (38.10mm x 50.00mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.500" Dia x 1.969" L (38.10mm x 50.00mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.500" Dia x 1.969" L (38.10mm x 50.00mm)
		Report errors?

180FM Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

180FM Payment Methods





















180FM Shipping Methods













If you have any question about 180FM, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com