



18127C104KAT2A Information



For Reference Only

Part Number 18127C104KAT2A Manufacturer AVX Corporation

Category Capacitors

Ceramic Capacitors

Description CAP CER 0.1UF 500V X7R 1812

Package 1812 (4532 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









18127C104KAT2A Specifications

Manufacturer Part Number 18127C104KAT2A Manufacturer AVX Corporation Category Capacitors Package 1812 (4532 Metric) Series - Capacitance 0.1 µF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose
Category Capacitors Package 1812 (4532 Metric) Series - Capacitance 0.1μF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose
Ceramic CapacitorsPackage $1812 (4532 \text{ Metric})$ Series-Capacitance $0.1 \mu F$ Tolerance $\pm 10\%$ Voltage - Rated $500V$ Temperature Coefficient $X7R$ Operating Temperature -55° C ~ 125° CFeatures-Ratings-ApplicationsGeneral Purpose
Package $1812 (4532 \text{ Metric})$ Series-Capacitance $0.1 \mu F$ Tolerance $\pm 10\%$ Voltage - Rated $500V$ Temperature Coefficient $X7R$ Operating Temperature -55° C ~ 125° CFeatures-Ratings-ApplicationsGeneral Purpose
Series - Capacitance $0.1\mu F$ Tolerance $\pm 10\%$ Voltage - Rated $500V$ Temperature Coefficient $X7R$ Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ Features - Capacitance -
Capacitance $0.1\mu F$ Tolerance $\pm 10\%$ Voltage - Rated $500V$ Temperature Coefficient $X7R$ Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ Features Ratings Applications General Purpose
Tolerance $\pm 10\%$ Voltage - Rated $500V$ Temperature Coefficient $X7R$ Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ Features - Ratings - Applications General Purpose
Voltage - Rated Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications South
Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose
Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose
Features - Ratings - Applications General Purpose
Ratings - Applications General Purpose
Applications General Purpose
Failure Rate -
Mounting Type Surface Mount, MLCC
Package / Case 1812 (4532 Metric)
Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm)
Height - Seated (Max)
Thickness (Max) 0.110" (2.79mm)
Lead Spacing -
Lead Style -
Report errors

18127C104KAT2A Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

18127C104KAT2A Payment Methods

































If you have any question about 18127C104KAT2A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com