



1812J0160333FCR Information

Heisener.com

Part Number 1812J0160333FCR
Manufacturer Knowles Syfer
Category Capacitors

Ceramic Capacitors

Description CAP CER 0.033UF 16V C0G/NP0 1812

Package 1812 (4532 Metric)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









1812J0160333FCR Specifications

Manufacturer Knowles Syfer Category Capacitors Package 1812 (4532 Metric) Series - Capacitance 0.033μF Tolerance ±1% Voltage - Rated 16V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric)		
Category Capacitors Package 1812 (4532 Metric) Series - Capacitance 0.033µF Tolerance ±1% Voltage - Rated 16V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric)	Manufacturer Part Number	1812J0160333FCR
Ceramic Capacitors Package 1812 (4532 Metric) Series - Capacitance 0.033μF Tolerance ±1% Voltage - Rated 16V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric)	Manufacturer	Knowles Syfer
Package 1812 (4532 Metric) Series - Capacitance 0.033μF Tolerance ±1% Voltage - Rated 16V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric)	Category	Capacitors
Series - Capacitance 0.033μF Tolerance ±1% Voltage - Rated 16V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric)		Ceramic Capacitors
Capacitance $0.033\mu F$ Tolerance $\pm 1\%$ Voltage - Rated $16V$ Temperature Coefficient COG , NP0Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ FeaturesEpoxy MountableRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case $1812 (4532 Metric)$	Package	1812 (4532 Metric)
Tolerance ±1% Voltage - Rated 16V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric)	Series	-
Voltage - Rated Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric)	Capacitance	0.033μF
Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric)	Tolerance	±1%
Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric)	Voltage - Rated	16V
Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric)	Temperature Coefficient	C0G, NP0
Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric)	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric)	Features	Epoxy Mountable
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric)	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric)	Applications	General Purpose
Package / Case 1812 (4532 Metric)	Failure Rate	-
	Mounting Type	Surface Mount, MLCC
	Package / Case	1812 (4532 Metric)
Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm)	Size / Dimension	0.177" L x 0.126" W (4.50mm x 3.20mm)
Height - Seated (Max) -	Height - Seated (Max)	-
Thickness (Max) 0.098" (2.50mm)	Thickness (Max)	0.098" (2.50mm)
Lead Spacing -	Lead Spacing	-
Lead Style -	Lead Style	-
Report errors?		Report errors?

1812J0160333FCR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

1812J0160333FCR Payment Methods



















1812J0160333FCR Shipping Methods













If you have any question about 1812J0160333FCR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com