



1812Y0100154JXT Information

Heisener.com

Part Number 1812Y0100154JXT

Manufacturer Knowles Syfer

Category Capacitors

Ceramic Capacitors

Description CAP CER 0.15UF 10V X7R 1812

Package 1812 (4532 Metric)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









1812Y0100154JXT Specifications

Manufacturer Part Number1812Y0100154JXTManufacturerKnowles SyferCategoryCapacitorsPackageCeramic CapacitorsPackage1812 (4532 Metric)SeriesFlexiCap?Capacitance0.15μFTolerance±5%Voltage - Rated10VTemperature CoefficientX7R (2R1)Operating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-
Category Capacitors Ceramic Capacitors Package $1812 (4532 \text{ Metric})$ Series FlexiCap? Capacitance $0.15\mu\text{F}$ Tolerance $\pm 5\%$ Voltage - Rated 10V Temperature Coefficient $X7R (2R1)$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Features Soft Termination
Ceramic CapacitorsPackage $1812 (4532 \text{ Metric})$ SeriesFlexiCap?Capacitance $0.15\mu\text{F}$ Tolerance $\pm 5\%$ Voltage - Rated 10V Temperature Coefficient $X7R (2R1)$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ FeaturesSoft Termination
Package $1812 (4532 \text{Metric})$ SeriesFlexiCap?Capacitance $0.15 \mu \text{F}$ Tolerance $\pm 5\%$ Voltage - Rated 10V Temperature Coefficient $X7R (2R1)$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ FeaturesSoft Termination
Series FlexiCap? Capacitance $0.15\mu F$ Tolerance $\pm 5\%$ Voltage - Rated $10V$ Temperature Coefficient $X7R$ (2R1) Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ Features Soft Termination
Capacitance $0.15\mu F$ Tolerance $\pm 5\%$ Voltage - Rated $10V$ Temperature Coefficient $X7R$ (2R1) Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ Features Soft Termination
Tolerance $\pm 5\%$ Voltage - Rated $10V$ Temperature Coefficient $X7R$ (2R1) Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ Features Soft Termination
Voltage - Rated Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination
Temperature Coefficient $X7R (2R1)$ Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ Features Soft Termination
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ Features Soft Termination
Features Soft Termination
Ratings -
Applications Boardflex Sensitive
Failure Rate -
Mounting Type Surface Mount, MLCC
Package / Case 1812 (4532 Metric)
Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm)
Height - Seated (Max)
Thickness (Max) 0.098" (2.50mm)
Lead Spacing -
Lead Style -
Report error

1812Y0100154JXT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

1812Y0100154JXT Payment Methods





















1812Y0100154JXT Shipping Methods













If you have any question about 1812Y0100154JXT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com