



1812Y0500333JDR Information

Heisener.com

Part Number 1812Y0500333JDR
Manufacturer Knowles Syfer
Category Capacitors

Ceramic Capacitors

Description CAP CER 0.033UF 50V X7R 1812

Package 1812 (4532 Metric)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









1812Y0500333JDR Specifications

| Manufacturer Part Number 1812Y0500333JDR Manufacturer Knowles Syfer Category Capacitors Package 1812 (4532 Metric) Series FlexiCap? Capacitance 0.033µF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style - Report errors? | | |
|---|--------------------------|---------------------------------------|
| Category Capacitors Package 1812 (4532 Metric) Series FlexiCap? Capacitance 0.033µF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style - | Manufacturer Part Number | 1812Y0500333JDR |
| Package 1812 (4532 Metric) Series FlexiCap? Capacitance 0.033μF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style - | Manufacturer | Knowles Syfer |
| Package 1812 (4532 Metric) Series FlexiCap? Capacitance 0.033µF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style - | Category | Capacitors |
| Series FlexiCap? Capacitance 0.033µF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style - | | Ceramic Capacitors |
| Capacitance 0.033μF Tolerance ±5% Voltage - Rated 50V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style - | Package | 1812 (4532 Metric) |
| Tolerance ±5% Voltage - Rated 50V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style - | Series | FlexiCap? |
| Voltage - Rated Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style | Capacitance | 0.033μF |
| Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style | Tolerance | ±5% |
| Operating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1812 (4532 Metric)Size / Dimension0.177" L x 0.126" W (4.50mm x 3.20mm)Height - Seated (Max)-Thickness (Max)0.098" (2.50mm)Lead Spacing-Lead Style- | Voltage - Rated | 50V |
| Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style - | Temperature Coefficient | X7R (2R1) |
| Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style | Operating Temperature | -55°C ~ 125°C |
| Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style - | Features | Soft Termination |
| Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style - | Ratings | - |
| Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style - | Applications | Boardflex Sensitive |
| Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style - | Failure Rate | - |
| Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style - | Mounting Type | Surface Mount, MLCC |
| Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - - | Package / Case | 1812 (4532 Metric) |
| Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style - | Size / Dimension | 0.177" L x 0.126" W (4.50mm x 3.20mm) |
| Lead Spacing - Lead Style - | Height - Seated (Max) | - |
| Lead Style - | Thickness (Max) | 0.098" (2.50mm) |
| · | Lead Spacing | - |
| Report errors? | Lead Style | - |
| | | Report errors? |

1812Y0500333JDR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

1812Y0500333JDR Payment Methods



















1812Y0500333JDR Shipping Methods













If you have any question about 1812Y0500333JDR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com