



#### 1812Y0630223FCT Information

Heisener.com

Category

Part Number

1812Y0630223FCT

Manufacturer Knowles Syfer Capacitors

Ceramic Capacitors

**Description** CAP CER 0.022UF 63V C0G/NP0 1812

**Package** 1812 (4532 Metric)

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 1812Y0630223FCT Specifications

Manufacturer Part Number         1812Y0630223FCT           Manufacturer         Knowles Syfer           Category         Capacitors           Package         1812 (4532 Metric)           Series         FlexiCap?           Capacitance         0.022µF           Tolerance         ±1%           Voltage - Rated         63V           Temperature Coefficient         C0G, NPO           Operating Temperature         -55°C ~ 125°C           Features         Soft Termination           Ratings         -           Applications         Boardflex Sensitive           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1812 (4532 Metric)           Size / Dimension         0.177" L x 0.126" W (4.50mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         0.098" (2.50mm)           Lead Spacing         -           Lead Style         -           Report errors?		
Category         Capacitors           Package         1812 (4532 Metric)           Series         FlexiCap?           Capacitance         0.022μF           Tolerance         ±1%           Voltage - Rated         63V           Temperature Coefficient         C0G, NPO           Operating Temperature         -55°C ~ 125°C           Features         Soft Termination           Ratings         -           Applications         Boardflex Sensitive           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1812 (4532 Metric)           Size / Dimension         0.177" L x 0.126" W (4.50mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         0.098" (2.50mm)           Lead Spacing         -           Lead Style         -	Manufacturer Part Number	1812Y0630223FCT
Package         1812 (4532 Metric)           Series         FlexiCap?           Capacitance         0.022µF           Tolerance         ±1%           Voltage - Rated         63V           Temperature Coefficient         COG, NPO           Operating Temperature         -55°C ~ 125°C           Features         Soft Termination           Ratings         -           Applications         Boardflex Sensitive           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1812 (4532 Metric)           Size / Dimension         0.177" L x 0.126" W (4.50mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         0.098" (2.50mm)           Lead Spacing         -           Lead Style         -	Manufacturer	Knowles Syfer
Package         1812 (4532 Metric)           Series         FlexiCap?           Capacitance         0.022μF           Tolerance         ±1%           Voltage - Rated         63V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Soft Termination           Ratings         -           Applications         Boardflex Sensitive           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1812 (4532 Metric)           Size / Dimension         0.177" L x 0.126" W (4.50mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         0.098" (2.50mm)           Lead Spacing         -           Lead Style         -	Category	Capacitors
Series         FlexiCap?           Capacitance         0.022μF           Tolerance         ±1%           Voltage - Rated         63V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Soft Termination           Ratings         -           Applications         Boardflex Sensitive           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1812 (4532 Metric)           Size / Dimension         0.177" L x 0.126" W (4.50mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         0.098" (2.50mm)           Lead Spacing         -           Lead Style         -		Ceramic Capacitors
Capacitance         0.022μF           Tolerance         ±1%           Voltage - Rated         63 V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Soft Termination           Ratings         -           Applications         Boardflex Sensitive           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1812 (4532 Metric)           Size / Dimension         0.177" L x 0.126" W (4.50mm x 3.20mm)           Height - Seated (Max)         -           Thickness (Max)         0.098" (2.50mm)           Lead Spacing         -           Lead Style         -	Package	1812 (4532 Metric)
Tolerance ±1%  Voltage - Rated 63V  Temperature Coefficient C0G, NP0  Operating Temperature -55°C ~ 125°C  Features Soft Termination  Ratings - Applications Boardflex Sensitive  Failure Rate - Mounting Type Surface Mount, MLCC  Package / Case 1812 (4532 Metric)  Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm)  Height - Seated (Max) -  Thickness (Max) 0.098" (2.50mm)  Lead Spacing -  Lead Style -	Series	FlexiCap?
Voltage - Rated63 VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1812 (4532 Metric)Size / Dimension0.177" L x 0.126" W (4.50mm x 3.20mm)Height - Seated (Max)-Thickness (Max)0.098" (2.50mm)Lead Spacing-Lead Style-	Capacitance	0.022μF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) Thickness (Max) 0.098" (2.50mm)  Lead Spacing Lead Style -	Tolerance	±1%
Operating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1812 (4532 Metric)Size / Dimension0.177" L x 0.126" W (4.50mm x 3.20mm)Height - Seated (Max)-Thickness (Max)0.098" (2.50mm)Lead Spacing-Lead Style-	Voltage - Rated	63V
Features  Soft Termination  Ratings  Applications  Boardflex Sensitive  Failure Rate  - Mounting Type Surface Mount, MLCC  Package / Case 1812 (4532 Metric)  Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm)  Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm)  Lead Spacing - Lead Style -	Temperature Coefficient	C0G, NP0
Ratings - Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style	Operating Temperature	-55°C ~ 125°C
Applications  Boardflex Sensitive  Failure Rate  - Mounting Type Surface Mount, MLCC  Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm)  Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm)  Lead Spacing - Lead Style -	Features	Soft Termination
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Applications	Boardflex Sensitive
Package / Case       1812 (4532 Metric)         Size / Dimension       0.177" L x 0.126" W (4.50mm x 3.20mm)         Height - Seated (Max)       -         Thickness (Max)       0.098" (2.50mm)         Lead Spacing       -         Lead Style       -	Failure Rate	-
Size / Dimension       0.177" L x 0.126" W (4.50mm x 3.20mm)         Height - Seated (Max)       -         Thickness (Max)       0.098" (2.50mm)         Lead Spacing       -         Lead Style       -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)  Thickness (Max)  Lead Spacing  Lead Style  -  -  -  -  -  -  -  -  -  -  -  -  -	Package / Case	1812 (4532 Metric)
Thickness (Max) 0.098" (2.50mm)  Lead Spacing -  Lead Style -	Size / Dimension	0.177" L x 0.126" W (4.50mm x 3.20mm)
Lead Spacing-Lead Style-	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.098" (2.50mm)
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

#### 1812Y0630223FCT Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# 1812Y0630223FCT Payment Methods



















### 1812Y0630223FCT Shipping Methods













If you have any question about 1812Y0630223FCT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com