



1812Y5000561JDR Information

Heisener.com

Part Number 1812Y5000561JDR
Manufacturer Knowles Syfer
Category Capacitors

Ceramic Capacitors

Description CAP CER 560PF 500V X7R 1812

Package 1812 (4532 Metric)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









1812Y5000561JDR Specifications

Manufacturer Part Number 1812Y5000561JDR Manufacturer Knowles Syfer Category Capacitors Package 1812 (4532 Metric) Series FlexiCap? Capacitance 560pF Tolerance ±5% Voltage - Rated 500V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style - Report errors?		
Category Capacitors Package 1812 (4532 Metric) Series FlexiCap? Capacitance 560pF Tolerance ±5% Voltage - Rated 500V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Manufacturer Part Number	1812Y5000561JDR
Package 1812 (4532 Metric) Series FlexiCap? Capacitance 560pF Tolerance ±5% Voltage - Rated 500V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Manufacturer	Knowles Syfer
Package 1812 (4532 Metric) Series FlexiCap? Capacitance 560pF Tolerance ±5% Voltage - Rated 500V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Category	Capacitors
Series FlexiCap? Capacitance 560pF Tolerance ±5% Voltage - Rated 500V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 560pF Tolerance ±5% Voltage - Rated 500V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Package	1812 (4532 Metric)
Tolerance ±5% Voltage - Rated 500V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Series	FlexiCap?
Voltage - Rated500VTemperature CoefficientX7R (2R1)Operating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1812 (4532 Metric)Size / Dimension0.177" L x 0.126" W (4.50mm x 3.20mm)Height - Seated (Max)-Thickness (Max)0.098" (2.50mm)Lead Spacing-Lead Style-	Capacitance	560pF
Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style	Tolerance	±5%
Operating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1812 (4532 Metric)Size / Dimension0.177" L x 0.126" W (4.50mm x 3.20mm)Height - Seated (Max)-Thickness (Max)0.098" (2.50mm)Lead Spacing-Lead Style-	Voltage - Rated	500V
Features Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension Height - Seated (Max) - Thickness (Max) Lead Spacing - Lead Style Soft Termination - Soft Termination - Ratings - Boardflex Sensitive - Boardflex Sensitive - Boardflex Sensitive - Boardflex Sensitive - 0.004 Surface Mount, MLCC - Su	Temperature Coefficient	X7R (2R1)
Ratings - Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style	Operating Temperature	-55°C ~ 125°C
Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Features	Soft Termination
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Applications	Boardflex Sensitive
Package / Case 1812 (4532 Metric) Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.177" L x 0.126" W (4.50mm x 3.20mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - -	Package / Case	1812 (4532 Metric)
Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Size / Dimension	0.177" L x 0.126" W (4.50mm x 3.20mm)
Lead Spacing-Lead Style-	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.098" (2.50mm)
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

1812Y5000561JDR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

1812Y5000561JDR Payment Methods

































If you have any question about 1812Y5000561JDR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com