

## 1817369 Information

Heisener.com

Part Number 1817369

Manufacturer Phoenix Contact

Category Connectors, Interconnects

Terminal Blocks - Headers, Plugs and Sockets

**Description** TERM BLOCK PLUG 15POS STR 3.5MM

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 1817369 Specifications

	Manufacturer Part Number	1817369
Category         Connectors, Interconnects           Terminal Blocks - Headers, Plugs and Sockets           Package         -           Series         COMBICON FK-MCP           Type         Plug, Female Sockets           Number of Positions         15           Positions Per Level         15           Number of Levels         1           Pitch         0.138" (3.50mm)           Header Orientation         -           Plug Wire Entry         180°           Termination Style         Screwless - Push-In Spring           Mounting Type         Free Hanging (In-Line)           Current - IEC         8A           Voltage - IEC         320V           Current - UL         8A           Voltage - UL         320V           Wire Gauge or Range - AWG         16-28 AWG           Wire Gauge or Range - mm²         0.14-1.5mm²	Manufacturer	
Terminal Blocks - Headers, Plugs and Sockets		
Package   -		
Series         COMBICON FK-MCP           Type         Plug, Female Sockets           Number of Positions         15           Positions Per Level         15           Number of Levels         1           Pitch         0.138" (3.50mm)           Header Orientation         -           Plug Wire Entry         180°           Termination Style         Screwless - Push-In Spring           Mounting Type         Free Hanging (In-Line)           Current - IEC         8A           Voltage - IEC         320V           Current - UL         8A           Voltage - UL         320V           Wire Gauge or Range - AWG         16-28 AWG           Wire Gauge or Range - mm²         0.14-1.5mm²	Package	_
Type         Plug, Female Sockets           Number of Positions         15           Positions Per Level         15           Number of Levels         1           Pitch         0.138" (3.50mm)           Header Orientation         -           Plug Wire Entry         180°           Termination Style         Screwless - Push-In Spring           Mounting Type         Free Hanging (In-Line)           Current - IEC         8A           Voltage - IEC         320V           Current - UL         8A           Voltage - UL         320V           Wire Gauge or Range - AWG         16-28 AWG           Wire Gauge or Range - mm²         0.14-1.5mm²		COMBICON FK-MCP
Number of Positions       15         Positions Per Level       15         Number of Levels       1         Pitch       0.138" (3.50mm)         Header Orientation       -         Plug Wire Entry       180°         Termination Style       Screwless - Push-In Spring         Mounting Type       Free Hanging (In-Line)         Current - IEC       8A         Voltage - IEC       320V         Current - UL       8A         Voltage - UL       320V         Wire Gauge or Range - AWG       16-28 AWG         Wire Gauge or Range - mm²       0.14-1.5mm²		
Positions Per Level   15   1   15   16   16   16   16   16		-
Number of Levels       1         Pitch       0.138" (3.50mm)         Header Orientation       -         Plug Wire Entry       180°         Termination Style       Screwless - Push-In Spring         Mounting Type       Free Hanging (In-Line)         Current - IEC       8A         Voltage - IEC       320V         Current - UL       8A         Voltage - UL       320V         Wire Gauge or Range - AWG       16-28 AWG         Wire Gauge or Range - mm²       0.14-1.5mm²		
Pitch       0.138" (3.50mm)         Header Orientation       -         Plug Wire Entry       180°         Termination Style       Screwless - Push-In Spring         Mounting Type       Free Hanging (In-Line)         Current - IEC       8A         Voltage - IEC       320V         Current - UL       8A         Voltage - UL       320V         Wire Gauge or Range - AWG       16-28 AWG         Wire Gauge or Range - mm²       0.14-1.5mm²		
Header Orientation - Plug Wire Entry - 180° Termination Style - Screwless - Push-In Spring Mounting Type - Free Hanging (In-Line)  Current - IEC - 8A - Voltage - IEC - 320V - Current - UL - 8A - Voltage - UL - 320V - Wire Gauge or Range - AWG - 16-28 AWG - Wire Gauge or Range - mm² - 0.14-1.5mm²		
Plug Wire Entry  Termination Style  Screwless - Push-In Spring  Mounting Type  Free Hanging (In-Line)  Current - IEC  8A  Voltage - IEC  320V  Current - UL  8A  Voltage - UL  320V  Wire Gauge or Range - AWG  Wire Gauge or Range - mm²  0.14-1.5mm²		
Termination Style  Mounting Type Free Hanging (In-Line)  Current - IEC  8A  Voltage - IEC  320V  Current - UL  8A  Voltage - UL  320V  Wire Gauge or Range - AWG  Wire Gauge or Range - mm²  0.14-1.5mm²		
Mounting Type         Free Hanging (In-Line)           Current - IEC         8A           Voltage - IEC         320V           Current - UL         8A           Voltage - UL         320V           Wire Gauge or Range - AWG         16-28 AWG           Wire Gauge or Range - mm²         0.14-1.5mm²		
Current - IEC       8A         Voltage - IEC       320V         Current - UL       8A         Voltage - UL       320V         Wire Gauge or Range - AWG       16-28 AWG         Wire Gauge or Range - mm²       0.14-1.5mm²	•	
Voltage - IEC       320V         Current - UL       8A         Voltage - UL       320V         Wire Gauge or Range - AWG       16-28 AWG         Wire Gauge or Range - mm²       0.14-1.5mm²		
Current - UL       8A         Voltage - UL       320V         Wire Gauge or Range - AWG       16-28 AWG         Wire Gauge or Range - mm²       0.14-1.5mm²		
Voltage - UL  320V  Wire Gauge or Range - AWG  Wire Gauge or Range - mm²  0.14-1.5mm²	-	
Wire Gauge or Range - AWG  Wire Gauge or Range - mm <sup>2</sup> 16-28 AWG  0.14-1.5mm <sup>2</sup>		
Wire Gauge or Range - mm <sup>2</sup> 0.14-1.5mm <sup>2</sup>	-	
Color	· ·	
Operating Temperature -	Operating Temperature	
	Contact Mating Finish	
Contact Mating Philsh	Contact ividing finish	1111

Features	Ejector Latches, Retention Latches (Non-Wire Side)	
		Report errors?

#### **1817369 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 1817369 Payment Methods



















# 1817369 Shipping Methods













If you have any question about 1817369, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com