



1825J0100270GCR Information

Heisener.com

For Reference Only

Manufact Category

Part Number 1825J0100270GCR Manufacturer Knowles Syfer

Capacitors
Ceramic Capacitors

Description CAP CER 27PF 10V C0G/NP0 1825

Package 1825 (4564 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









1825J0100270GCR Specifications

Manufacturer Part Number 1825J0100270GCR Manufacturer Knowles Syfer Category Capacitors Package 1825 (4564 Metric) Series - Capacitance 27pF Tolerance ±2% Voltage - Rated 10V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Spacing - Lead Style -		
Category Capacitors Package 1825 (4564 Metric) Series - Capacitance 27pF Tolerance ±2% Voltage - Rated 10V Temperature Coefficient C0G, NPO Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Manufacturer Part Number	1825J0100270GCR
Package 1825 (4564 Metric) Series - Capacitance 27pF Tolerance ±2% Voltage - Rated 10V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Manufacturer	Knowles Syfer
Package 1825 (4564 Metric) Series - Capacitance 27pF Tolerance ±2% Voltage - Rated 10V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Category	Capacitors
Series - Capacitance 27pF Tolerance ±2% Voltage - Rated 10V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 27pF Tolerance ±2% Voltage - Rated 10V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Package	1825 (4564 Metric)
Tolerance ±2% Voltage - Rated 10V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Series	-
Voltage - Rated10VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1825 (4564 Metric)Size / Dimension0.177" L x 0.252" W (4.50mm x 6.40mm)Height - Seated (Max)-Thickness (Max)0.098" (2.50mm)Lead Spacing-Lead Style-	Capacitance	27pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Tolerance	±2%
Operating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1825 (4564 Metric)Size / Dimension0.177" L x 0.252" W (4.50mm x 6.40mm)Height - Seated (Max)-Thickness (Max)0.098" (2.50mm)Lead Spacing-Lead Style-	Voltage - Rated	10V
Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Temperature Coefficient	C0G, NP0
Ratings - General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Features	Epoxy Mountable
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Applications	General Purpose
Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - -	Package / Case	1825 (4564 Metric)
Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Size / Dimension	0.177" L x 0.252" W (4.50mm x 6.40mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.098" (2.50mm)
·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

1825J0100270GCR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

1825J0100270GCR Payment Methods



















1825J0100270GCR Shipping Methods













If you have any question about 1825J0100270GCR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com