



### 1825J0630181GCR Information

Heisener.com

Part Number 1825J0630181GCR
Manufacturer Knowles Syfer
Category Capacitors

**Ceramic Capacitors** 

**Description** CAP CER 180PF 63V C0G/NP0 1825

**Package** 1825 (4564 Metric)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 1825J0630181GCR Specifications

Manufacturer Part Number         1825J0630181GCR           Manufacturer         Knowles Syfer           Category         Capacitors           Package         1825 (4564 Metric)           Series         -           Capacitance         180pF           Tolerance         ±2%           Voltage - Rated         63V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Epoxy Mountable           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1825 (4564 Metric)           Size / Dimension         0.177" L x 0.252" W (4.50mm x 6.40mm)           Height - Seated (Max)         -           Thickness (Max)         0.098" (2.50mm)           Lead Spacing         -           Lead Spacing         -           Lead Style         -		
Category         Capacitors           Package         1825 (4564 Metric)           Series         -           Capacitance         180pF           Tolerance         ±2%           Voltage - Rated         63V           Temperature Coefficient         C0G, NPO           Operating Temperature         -55°C ~ 125°C           Features         Epoxy Mountable           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1825 (4564 Metric)           Size / Dimension         0.177" L x 0.252" W (4.50mm x 6.40mm)           Height - Seated (Max)         -           Thickness (Max)         0.098" (2.50mm)           Lead Spacing         -           Lead Style         -	Manufacturer Part Number	1825J0630181GCR
Package         1825 (4564 Metric)           Series         -           Capacitance         180pF           Tolerance         ±2%           Voltage - Rated         63V           Temperature Coefficient         COG, NPO           Operating Temperature         -55°C ~ 125°C           Features         Epoxy Mountable           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1825 (4564 Metric)           Size / Dimension         0.177" L x 0.252" W (4.50mm x 6.40mm)           Height - Seated (Max)         -           Thickness (Max)         0.098" (2.50mm)           Lead Spacing         -           Lead Style         -	Manufacturer	Knowles Syfer
Package         1825 (4564 Metric)           Series         -           Capacitance         180pF           Tolerance         ±2%           Voltage - Rated         63V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Epoxy Mountable           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1825 (4564 Metric)           Size / Dimension         0.177" L x 0.252" W (4.50mm x 6.40mm)           Height - Seated (Max)         -           Thickness (Max)         0.098" (2.50mm)           Lead Spacing         -           Lead Style         -	Category	Capacitors
Series         -           Capacitance         180pF           Tolerance         ±2%           Voltage - Rated         63V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Epoxy Mountable           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1825 (4564 Metric)           Size / Dimension         0.177" L x 0.252" W (4.50mm x 6.40mm)           Height - Seated (Max)         0.098" (2.50mm)           Lead Spacing         -           Lead Style         -		Ceramic Capacitors
Capacitance         180pF           Tolerance         ±2%           Voltage - Rated         63V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Epoxy Mountable           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1825 (4564 Metric)           Size / Dimension         0.177" L x 0.252" W (4.50mm x 6.40mm)           Height - Seated (Max)         -           Thickness (Max)         0.098" (2.50mm)           Lead Spacing         -           Lead Style         -	Package	1825 (4564 Metric)
Tolerance         ±2%           Voltage - Rated         63V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         Epoxy Mountable           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1825 (4564 Metric)           Size / Dimension         0.177" L x 0.252" W (4.50mm x 6.40mm)           Height - Seated (Max)         -           Thickness (Max)         0.098" (2.50mm)           Lead Spacing         -           Lead Style         -	Series	-
Voltage - Rated63 VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1825 (4564 Metric)Size / Dimension0.177" L x 0.252" W (4.50mm x 6.40mm)Height - Seated (Max)-Thickness (Max)0.098" (2.50mm)Lead Spacing-Lead Style-	Capacitance	180pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) Thickness (Max) 0.098" (2.50mm)  Lead Spacing - Lead Style -	Tolerance	±2%
Operating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1825 (4564 Metric)Size / Dimension0.177" L x 0.252" W (4.50mm x 6.40mm)Height - Seated (Max)-Thickness (Max)0.098" (2.50mm)Lead Spacing-Lead Style-	Voltage - Rated	63V
Features Epoxy Mountable  Ratings - Applications General Purpose  Failure Rate - Mounting Type Surface Mount, MLCC  Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm)  Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm)  Lead Spacing - Lead Style -	Temperature Coefficient	C0G, NP0
Ratings - General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Features	Epoxy Mountable
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Applications	General Purpose
Package / Case       1825 (4564 Metric)         Size / Dimension       0.177" L x 0.252" W (4.50mm x 6.40mm)         Height - Seated (Max)       -         Thickness (Max)       0.098" (2.50mm)         Lead Spacing       -         Lead Style       -	Failure Rate	-
Size / Dimension       0.177" L x 0.252" W (4.50mm x 6.40mm)         Height - Seated (Max)       -         Thickness (Max)       0.098" (2.50mm)         Lead Spacing       -         Lead Style       -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)  Thickness (Max)  Lead Spacing  Lead Style  -  -  -  -  -  -  -  -  -  -  -  -  -	Package / Case	1825 (4564 Metric)
Thickness (Max) 0.098" (2.50mm)  Lead Spacing -  Lead Style -	Size / Dimension	0.177" L x 0.252" W (4.50mm x 6.40mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.098" (2.50mm)
·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

### 1825J0630181GCR Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 1825J0630181GCR Payment Methods



















### 1825J0630181GCR Shipping Methods













If you have any question about 1825J0630181GCR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com