



1825J5000224KXR Information

Heisener.com

1825J5000224KXR Part Number Manufacturer Knowles Syfer Category

Capacitors **Ceramic Capacitors**

Description CAP CER 0.22UF 500V X7R 1825

Package 1825 (4564 Metric)

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









1825J5000224KXR Specifications

Manufacturer Part Number 1825J5000224KXR Manufacturer Knowles Syfer Category Capacitors Package 1825 (4564 Metric) Series - Capacitance 0.22µF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications Automotive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Spacing - Lead Style -		
Category Capacitors Package 1825 (4564 Metric) Series - Capacitance 0.22μF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications Automotive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Manufacturer Part Number	1825J5000224KXR
Package 1825 (4564 Metric) Series - Capacitance 0.22µF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications Automotive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Manufacturer	Knowles Syfer
Package 1825 (4564 Metric) Series - Capacitance 0.22µF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications Automotive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Category	Capacitors
Series - Capacitance 0.22µF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications Automotive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 0.22μF Tolerance ±10% Voltage - Rated 500V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications Automotive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Package	1825 (4564 Metric)
Tolerance ±10% Voltage - Rated 500V Temperature Coefficient X7R (2R1) Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications Automotive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Series	-
Voltage - Rated500VTemperature CoefficientX7R (2R1)Operating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsAutomotiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1825 (4564 Metric)Size / Dimension0.177" L x 0.252" W (4.50mm x 6.40mm)Height - Seated (Max)-Thickness (Max)0.098" (2.50mm)Lead Spacing-Lead Style-	Capacitance	0.22μF
Temperature Coefficient ATR (2R1) Operating Temperature -55°C ~ 125°C Features Epoxy Mountable Ratings - Applications Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeaturesEpoxy MountableRatings-ApplicationsAutomotiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1825 (4564 Metric)Size / Dimension0.177" L x 0.252" W (4.50mm x 6.40mm)Height - Seated (Max)-Thickness (Max)0.098" (2.50mm)Lead Spacing-Lead Style-	Voltage - Rated	500V
Features Epoxy Mountable Ratings - Applications Automotive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Temperature Coefficient	X7R (2R1)
Ratings - Automotive Failure Rate - Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style	Operating Temperature	-55°C ~ 125°C
Applications Automotive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Features	Epoxy Mountable
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Applications	Automotive
Package / Case 1825 (4564 Metric) Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm) Height - Seated (Max) - Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - -	Package / Case	1825 (4564 Metric)
Thickness (Max) 0.098" (2.50mm) Lead Spacing - Lead Style -	Size / Dimension	0.177" L x 0.252" W (4.50mm x 6.40mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.098" (2.50mm)
·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

1825J5000224KXR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

1825J5000224KXR Payment Methods



















1825J5000224KXR Shipping Methods













If you have any question about 1825J5000224KXR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com