



1825Y2000471JCT Information

Heisener.com

Part Number 1825Y2000471JCT
Manufacturer Knowles Syfer
Category Capacitors

Ceramic Capacitors

Description CAP CER 470PF 200V C0G/NP0 1825

Package 1825 (4564 Metric)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









1825Y2000471JCT Specifications

Manufacturer Part Number1825Y2000471JCTManufacturerKnowles SyferCategoryCapacitorsPackage1825 (4564 Metric)SeriesFlexiCap?Capacitance470pFTolerance±5%Voltage - Rated200VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCC
Category Capacitors Package 1825 (4564 Metric) Series FlexiCap? Capacitance 470pF Tolerance ±5% Voltage - Rated 200V Temperature Coefficient Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Failure Rate - Capacitors Capacitors FlexiCap? 470pF 200V Cog, NP0 Cog, NP0 Cog, NP0 Boardflex Sensitive Failure Rate -
Ceramic Capacitors Package 1825 (4564 Metric) Series FlexiCap? Capacitance 470pF Tolerance ±5% Voltage - Rated 200V Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate -
Package 1825 (4564 Metric) Series FlexiCap? Capacitance 470pF Tolerance ±5% Voltage - Rated 200V Temperature Coefficient COG, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate -
Series FlexiCap? Capacitance 470pF Tolerance ±5% Voltage - Rated 200V Temperature Coefficient COG, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate -
Capacitance 470pF Tolerance ±5% Voltage - Rated 200V Temperature Coefficient C0G, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate -
Tolerance $\pm 5\%$ Voltage - Rated $200V$ Temperature Coefficient $C0G$, NP0 Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate -
Voltage - Rated 200V Temperature Coefficient COG, NP0 Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate -
Temperature Coefficient COG, NPO Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate -
Operating Temperature -55°C ~ 125°C Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate -
Features Soft Termination Ratings - Applications Boardflex Sensitive Failure Rate -
Ratings - Applications Boardflex Sensitive Failure Rate -
Applications Boardflex Sensitive Failure Rate -
Failure Rate -
Mounting Type Surface Mount, MLCC
Package / Case 1825 (4564 Metric)
Size / Dimension 0.177" L x 0.252" W (4.50mm x 6.40mm)
Height - Seated (Max) -
Thickness (Max) 0.098" (2.50mm)
Lead Spacing -
Lead Style -
Report errors?

1825Y2000471JCT Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

1825Y2000471JCT Payment Methods





















1825Y2000471JCT Shipping Methods













If you have any question about 1825Y2000471JCT, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com