

182G18 Information

Heisener.com

Part Number 182G18

Manufacturer Hammond Manufacturing

Category Transformers

Power Transformers

Description XFRMR TOROIDAL 225VA CHAS MOUNT

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









182G18 Specifications

Manufacturer Part Number 182G18 Manufacturer Hammond Manufacturing Category Transformers Power Transformers Power Transformers Series 182 Type Toroidal Voltage - Primary 117V, 234V Voltage - Secondary (Full Load) Parallel 18V, Series 36V Current - Output (Max) Parallel 12.5A, Series 6.25A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 225 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension - Height - Seated (Max) 48.26mm Voltage - Isolation 4000Vrms Weight 5 lbs (2.3kg)		
Category Transformers Package - Series 182 Type Toroidal Voltage - Primary 117V, 234V Voltage - Secondary (Full Load) Parallel 18V, Series 36V Current - Output (Max) Parallel 12.5A, Series 6.25A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 225 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension - Height - Seated (Max) 48.26mm Voltage - Isolation 4000Vrms Weight 5 lbs (2.3kg)	Manufacturer Part Number	182G18
Package Package Package Package Package Package Primary Poltage - Primary Poltage - Secondary (Full Load) Parallel 18V, Series 36V Primary Winding(s) Parallel 12.5A, Series 6.25A Primary Winding(s) Pual Secondary Winding(s) Pual Center Tap No Power - Max Package Primary Power - Max Primary Power - Max Package Primary Power - Max	Manufacturer	Hammond Manufacturing
Package-Series182TypeToroidalVoltage - Primary117V, 234VVoltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)Parallel 12.5A, Series 6.25APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max225 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension-Height - Seated (Max)48.26mmVoltage - Isolation4000VrmsWeight5 lbs (2.3kg)	Category	Transformers
Series182TypeToroidalVoltage - Primary117V, 234VVoltage - Secondary (Full Load)Parallel 18V, Series 36VCurrent - Output (Max)Parallel 12.5A, Series 6.25APrimary Winding(s)DualSecondary Winding(s)DualCenter TapNoPower - Max225 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension-Height - Seated (Max)48.26mmVoltage - Isolation4000VrmsWeight5 lbs (2.3kg)		Power Transformers
Type Toroidal Voltage - Primary 117V, 234V Voltage - Secondary (Full Load) Parallel 18V, Series 36V Current - Output (Max) Parallel 12.5A, Series 6.25A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 225 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension - Height - Seated (Max) 48.26mm Voltage - Isolation 4000Vrms Weight 5 lbs (2.3kg)	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 18V, Series 36V Current - Output (Max) Parallel 12.5A, Series 6.25A Primary Winding(s) Dual Secondary Winding(s) Center Tap No Power - Max 225 VA Mounting Type Chassis Mount Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Weight 117V, 234V Parallel 18V, Series 36V Parallel 12.5A, Series 6.25A Parallel 18V, Series 36V Parallel 18V, Series 40.25A Parallel 18V, Series 40.25A Parallel 18V, Series 36V Parallel 18V, Series 40.25A Parallel 18V, Series 40.25A Parallel 18V, Series 40.25A Parallel 12.5A, Series 6.25A Pull Parallel 18V, Series 36V Parallel 12.5A, Series 6.25A Pull Parallel 18V, Series 36V Parallel 12.5A, Series 6.25A Pull Parallel 12.5A, Series 6.25A Parallel 12.5A, Series 6.25A Parallel 12.5A, Series 6.25A Pull Par	Series	182
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 12.5A, Series 36V Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max Mounting Type Chassis Mount Termination Style Size / Dimension - Height - Seated (Max) Weight Parallel 18V, Series 36V Parallel 12.5A, Series 6.25A Primary Winding (s) Dual No Chassis Mount Wire Leads 425 VA Wire Leads 48.26mm 4000Vrms 4000Vrms 5 lbs (2.3kg)	Type	Toroidal
Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 225 VA Mounting Type Chassis Mount Termination Style Size / Dimension - Height - Seated (Max) Voltage - Isolation Weight Parallel 12.5A, Series 6.25A Dual Dual No Powal No Powal Au Au Au Au Au Au Au Au Au A	Voltage - Primary	117V, 234V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max 225 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension - Height - Seated (Max) Voltage - Isolation Weight Dual Au Au Au Au Au Au Au Au Au A	Voltage - Secondary (Full Load)	Parallel 18V, Series 36V
Secondary Winding(s)DualCenter TapNoPower - Max225 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension-Height - Seated (Max)48.26mmVoltage - Isolation4000VrmsWeight5 lbs (2.3kg)	Current - Output (Max)	Parallel 12.5A, Series 6.25A
Center Tap No Power - Max 225 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension - Height - Seated (Max) 48.26mm Voltage - Isolation 4000Vrms Weight 5 lbs (2.3kg)	Primary Winding(s)	Dual
Power - Max Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension - Height - Seated (Max) Voltage - Isolation Weight 225 VA Wire Leads 48.26mm 4000Vrms 5 lbs (2.3kg)	Secondary Winding(s)	Dual
Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension - Height - Seated (Max) 48.26mm Voltage - Isolation 4000Vrms Weight 5 lbs (2.3kg)	Center Tap	No
Termination Style Wire Leads Size / Dimension - Height - Seated (Max) 48.26mm Voltage - Isolation 4000Vrms Weight 5 lbs (2.3kg)	Power - Max	225 VA
Size / Dimension - Height - Seated (Max) 48.26mm Voltage - Isolation 4000Vrms Weight 5 lbs (2.3kg)	Mounting Type	Chassis Mount
Height - Seated (Max) Voltage - Isolation Weight 48.26mm 4000Vrms 5 lbs (2.3kg)	Termination Style	Wire Leads
Voltage - Isolation 4000Vrms Weight 5 lbs (2.3kg)	Size / Dimension	-
Weight 5 lbs (2.3kg)	Height - Seated (Max)	48.26mm
	Voltage - Isolation	4000Vrms
D ()	Weight	5 lbs (2.3kg)
Report errors?		Report errors?

182G18 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

182G18 Payment Methods



















182G18 Shipping Methods













If you have any question about 182G18, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com