

182R30 Information

Heisener.com

Part Number 182R30

Manufacturer Hammond Manufacturing

Category Transformers

Power Transformers

Description XFRMR TOROIDAL 500VA CHAS MOUNT

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









182R30 Specifications

Manufacturer Part Number 182R30 Manufacturer Hammond Manufacturing Category Transformers Package - Series 182 Type Toroidal Voltage - Primary 117V, 234V Voltage - Secondary (Full Load) Parallel 30V, Series 60V Current - Output (Max) Parallel 16.66A, Series 8.33A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 500 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension - Height - Seated (Max) 56.13mm Voltage - Isolation 4000Vrms Weight 8.5 lbs (3.9kg)		
Category Transformers Power Transformers Package - Series 182 Type Toroidal Voltage - Primary 117V, 234V Voltage - Secondary (Full Load) Parallel 30V, Series 60V Current - Output (Max) Parallel 16.66A, Series 8.33A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 500 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension - Height - Seated (Max) 56.13mm Voltage - Isolation 4000Vrms	Manufacturer Part Number	182R30
Package - Series 182 Type Toroidal Voltage - Primary 117V, 234V Voltage - Secondary (Full Load) Parallel 30V, Series 60V Current - Output (Max) Parallel 16.66A, Series 8.33A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 500 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension - Height - Seated (Max) Voltage - Isolation 4000Vrms	Manufacturer	Hammond Manufacturing
Package - Series 182 Type Toroidal Voltage - Primary 117V, 234V Voltage - Secondary (Full Load) Parallel 30V, Series 60V Current - Output (Max) Parallel 16.66A, Series 8.33A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 500 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension - Height - Seated (Max) Voltage - Isolation 4000Vrms	Category	Transformers
Series 182 Type Toroidal Voltage - Primary 117V, 234V Voltage - Secondary (Full Load) Parallel 30V, Series 60V Current - Output (Max) Parallel 16.66A, Series 8.33A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 500 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension - Height - Seated (Max) 56.13mm Voltage - Isolation 4000Vrms		Power Transformers
Type Toroidal Voltage - Primary 117V, 234V Voltage - Secondary (Full Load) Parallel 30V, Series 60V Current - Output (Max) Parallel 16.66A, Series 8.33A Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max 500 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension - Height - Seated (Max) 56.13mm Voltage - Isolation 4000Vrms	Package	-
Voltage - Primary Voltage - Secondary (Full Load) Parallel 30V, Series 60V Current - Output (Max) Parallel 16.66A, Series 8.33A Primary Winding(s) Dual Secondary Winding(s) Center Tap No Power - Max 500 VA Mounting Type Chassis Mount Termination Style Size / Dimension - Height - Seated (Max) Voltage - Isolation 117V, 234V Parallel 30V, Series 60V Parallel 16.66A, Series 8.33A Dual Chassis Mount Under Chassis Mount - Hought - Seated (Max) Voltage - Isolation 4000Vrms	Series	182
Voltage - Secondary (Full Load) Current - Output (Max) Parallel 16.66A, Series 8.33A Primary Winding(s) Dual Secondary Winding(s) Center Tap No Power - Max 500 VA Mounting Type Chassis Mount Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Parallel 30V, Series 60V Parallel 16.66A, Series 8.33A Dual Secondary Winding(s) Dual Secondary Winding(s) Dual Secondary Winding(s) For all calls and c	Type	Toroidal
Current - Output (Max) Primary Winding(s) Dual Secondary Winding(s) Dual Center Tap No Power - Max Mounting Type Chassis Mount Termination Style Size / Dimension Height - Seated (Max) Voltage - Isolation Parallel 16.66A, Series 8.33A Dual Dual Chassis Mount Voltage - Isolation Parallel 16.66A, Series 8.33A Dual Dual Chassis Mount Style Wire Leads 500 VA Wire Leads 513mm 4000Vrms	Voltage - Primary	117V, 234V
Primary Winding(s) Secondary Winding(s) Dual Center Tap No Power - Max Mounting Type Chassis Mount Termination Style Size / Dimension	Voltage - Secondary (Full Load)	Parallel 30V, Series 60V
Secondary Winding(s) Center Tap No Power - Max 500 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension - Height - Seated (Max) Voltage - Isolation Dual No Chassis Mount 500 VA Chassis Mount 500 VA 4000 Vrms	Current - Output (Max)	Parallel 16.66A, Series 8.33A
Center TapNoPower - Max500 VAMounting TypeChassis MountTermination StyleWire LeadsSize / Dimension-Height - Seated (Max)56.13mmVoltage - Isolation4000Vrms	Primary Winding(s)	Dual
Power - Max 500 VA Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension - Height - Seated (Max) 56.13mm Voltage - Isolation 4000Vrms	Secondary Winding(s)	Dual
Mounting Type Chassis Mount Termination Style Wire Leads Size / Dimension - Height - Seated (Max) 56.13mm Voltage - Isolation 4000Vrms	Center Tap	No
Termination Style Wire Leads Size / Dimension - Height - Seated (Max) 56.13mm Voltage - Isolation 4000Vrms	Power - Max	500 VA
Size / Dimension - Height - Seated (Max) 56.13mm Voltage - Isolation 4000Vrms	Mounting Type	Chassis Mount
Height - Seated (Max) 56.13mm Voltage - Isolation 4000Vrms	Termination Style	Wire Leads
Voltage - Isolation 4000Vrms	Size / Dimension	-
	Height - Seated (Max)	56.13mm
Weight 8.5 lbs (3.9kg)	Voltage - Isolation	4000Vrms
	Weight	8.5 lbs (3.9kg)
Report errors?		Report errors?

182R30 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

182R30 Payment Methods



















182R30 Shipping Methods













If you have any question about 182R30, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com