

1840466-1 Information

Heisener.com

Part Number 1840466-1

Manufacturer TRP Connector B.V.

Category Connectors, Interconnects

Modular Connectors - Jacks With Magnetics

Description CONN MAGJACK 1PORT 1000 BASE-T

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









1840466-1 Specifications

Manufacturer Part Number 1840466-1 Manufacturer TRP Connector B.V. Category Connectors, Interconnects Modular Connectors - Jacks With Magnetics Package - Series MagJack? Connector Type RJ45 Number of Ports 1 Number of Rows 1 Applications 10/100/1000 Base-T, AutoMDIX Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 0.555" (14.10mm) LED Color Does Not Contain LED Number of Cores per Jack 8 Shielding Shielded Features Board Guide Tab Direction Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C		
CategoryConnectors, InterconnectsModular Connectors - Jacks With MagneticsPackage-SeriesMagJack?Connector TypeRJ45Number of Ports1Number of Rows1Applications10/100/1000 Base-T, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.555" (14.10mm)LED ColorDoes Not Contain LEDNumber of Cores per Jack8ShieldingShieldedFeaturesBoard GuideTab DirectionDownContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Manufacturer Part Number	1840466-1
Package-SeriesMagJack?Connector TypeRJ45Number of Ports1Number of Rows1Applications10/100/1000 Base-T, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.555" (14.10mm)LED ColorDoes Not Contain LEDNumber of Cores per Jack8ShieldingShieldedFeaturesBoard GuideTab DirectionDownContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Manufacturer	TRP Connector B.V.
Package-SeriesMagJack?Connector TypeRJ45Number of Ports1Number of Rows1Applications10/100/1000 Base-T, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.555" (14.10mm)LED ColorDoes Not Contain LEDNumber of Cores per Jack8ShieldingShieldedFeaturesBoard GuideTab DirectionDownContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Category	Connectors, Interconnects
Series MagJack? Connector Type RJ45 Number of Ports 1 Number of Rows 1 Applications 10/100/1000 Base-T, AutoMDIX Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 0.555" (14.10mm) LED Color Does Not Contain LED Number of Cores per Jack 8 Shielding Shielded Features Board Guide Tab Direction Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C		Modular Connectors - Jacks With Magnetics
Connector Type RJ45 Number of Ports 1 Number of Rows 1 Applications 10/100/1000 Base-T, AutoMDIX Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 0.555" (14.10mm) LED Color Does Not Contain LED Number of Cores per Jack 8 Shielding Shielded Features Board Guide Tab Direction Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature	Package	-
Number of Ports 1 Number of Rows 1 Applications 10/100/1000 Base-T, AutoMDIX Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board 0.555" (14.10mm) LED Color Does Not Contain LED Number of Cores per Jack 8 Shielding Shielded Features Board Guide Tab Direction Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Series	MagJack?
Number of Rows1Applications10/100/1000 Base-T, AutoMDIXMounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.555" (14.10mm)LED ColorDoes Not Contain LEDNumber of Cores per Jack8ShieldingShieldedFeaturesBoard GuideTab DirectionDownContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Connector Type	RJ45
Applications Mounting Type Through Hole Orientation 90° Angle (Right) Termination Solder Height Above Board LED Color Number of Cores per Jack Shielding Shielded Features Board Guide Tab Direction Contact Material Phosphor Bronze Contact Finish Operating Temperature 10/100/1000 Base-T, AutoMDIX Through Hole 10/00/1000 Base-T, AutoMDIX AutoMDI	Number of Ports	1
Mounting TypeThrough HoleOrientation90° Angle (Right)TerminationSolderHeight Above Board0.555" (14.10mm)LED ColorDoes Not Contain LEDNumber of Cores per Jack8ShieldingShieldedFeaturesBoard GuideTab DirectionDownContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Number of Rows	1
Orientation 90° Angle (Right) Termination Solder Height Above Board 0.555" (14.10mm) LED Color Does Not Contain LED Number of Cores per Jack 8 Shielding Shielded Features Board Guide Tab Direction Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	Applications	10/100/1000 Base-T, AutoMDIX
Termination Solder Height Above Board 0.555" (14.10mm) LED Color Does Not Contain LED Number of Cores per Jack 8 Shielding Shielded Features Board Guide Tab Direction Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	Mounting Type	Through Hole
Height Above Board LED Color Does Not Contain LED Number of Cores per Jack 8 Shielding Shielded Features Board Guide Tab Direction Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	Orientation	90° Angle (Right)
LED ColorDoes Not Contain LEDNumber of Cores per Jack8ShieldingShieldedFeaturesBoard GuideTab DirectionDownContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature0°C ~ 70°C	Termination	Solder
Number of Cores per Jack Shielding Shielded Features Board Guide Tab Direction Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 8	Height Above Board	0.555" (14.10mm)
Shielding Shielded Features Board Guide Tab Direction Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature O°C ~ 70°C	LED Color	Does Not Contain LED
Features Board Guide Tab Direction Down Contact Material Phosphor Bronze Contact Finish Gold Operating Temperature 0°C ~ 70°C	Number of Cores per Jack	8
Tab DirectionDownContact MaterialPhosphor BronzeContact FinishGoldOperating Temperature 0° C ~ 70° C	Shielding	Shielded
Contact MaterialPhosphor BronzeContact FinishGoldOperating Temperature 0° C ~ 70° C	Features	Board Guide
Contact Finish Gold Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$	Tab Direction	Down
Operating Temperature $0^{\circ}\text{C} \sim 70^{\circ}\text{C}$	Contact Material	Phosphor Bronze
	Contact Finish	Gold
Report errors?	Operating Temperature	0°C ~ 70°C
		Report errors?

1840466-1 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

1840466-1 Payment Methods



















1840466-1 Shipping Methods













If you have any question about 1840466-1, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com